

Produktinformation



Dell UltraSharp U2421HE - LED monitor - Full HD (1080p) - 24"

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	DELL-U2421HE

Get a stable, wired connection to your network and peripherals on this sleek 23.8" QHD hub monitor with RJ45, USB-C and a host of other ports.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	24"
Viewable Size	23.8"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.2745 mm
Pixel Per Inch	92.5
Brightness	250 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	8 ms (normal); 5 ms (fast)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Bezel Type	Flat front
Features	99% sRGB colour gamut, daisy chain compatible, 99% Rec 709 colour gamut, 85% DCI-P3, Delta E<2 calibration

Dimensions (WxDxH) 53.85 cm x 16.51 cm x 34.798 cm - with stand

Connectivity

Interfaces DisplayPort (HDCP) HDMI (HDCP) USB-C 3.1 Gen 1 upstream/
DisplayPort with Power Delivery DisplayPort output (MST) 2 x USB 3.0
downstream 2 x USB 3.0 downstream with Battery Charging 1.2 Audio
line-out (mini-jack)

Mechanical

Display Position Adjustments Height, pivot (rotation), swivel, tilt

Tilt Angle -5/+21

Swivel Angle 80

Height Adjustment 130 mm

Miscellaneous

Features Security lock slot (cable lock sold separately), anti-theft stand lock slot

Cables Included 1 x DisplayPort cable - DisplayPort to DisplayPort 1 x USB-C cable

Compliant Standards RoHS, DisplayPort 1.4, HDCP 1.4

Power

Voltage Required AC 120/230 V (50/60 Hz)

Dimensions & Weight

Dimensions & Weight Details With stand - width: 53.85 cm - depth: 16.51 cm - height: 34.798 cm
Without stand - width: 53.85 cm - depth: 3.81 cm - height: 31.496 cm -
weight: 3.35 kg

Dimensions & Weight (Shipping)

Shipping Weight 7.55 kg

Environmental Standards

TCO Certified TCO Certified Displays 8

ENERGY STAR Certified Yes

Manufacturer Warranty

Bundled Services 3 years Advanced Exchange Service

Environmental Parameters

Min Operating Temperature 0 °C

Max Operating Temperature 40 °C

Humidity Range Operating 10 - 80% (non-condensing)