

Produktinformation



Dell UltraSharp UP2720Q - LED monitor - 4K - 27"

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	DELL-UP2720Q

With a convenient built-in colorimeter, you can calibrate your monitor on demand or on a schedule. Rest assured the display is color accurate and true to the color values you've chosen for a project's duration. Save valuable time and stay on task with Dell Calibration Assistant. Schedule automated color calibrations and validations, even after work hours. This monitor features a wide variety of tools designed to make every project seamless. Modify settings and color profiles, run calibration reports and more with Dell Color Management.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class B
Energy Consumption per Year	45 kWh
Power Consumption (On mode)	31 W
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	Calibration sensor, USB 3.2 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Pixel Pitch	0.1554 mm
Pixel Per Inch	163
Brightness	250 cd/m ²
Contrast Ratio	1300:1
Colour Support	1.07 billion colours
Response Time	8 ms (grey-to-grey normal); 6 ms (grey-to-grey fast)
Horizontal Viewing Angle	178

Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	WLED
Bezel Type	Flat front
Features	PremierColor technology, 100% Adobe RGB colour gamut, LED edgelight system, Factory Calibration, Colour Calibration, Factory Calibration Report, 98% DCI-P3, 80% BT.2020 colour gamut, Picture-by-Picture, Delta E<2 calibration, CalMAN Verified
Colour	Black
Dimensions (WxDxH)	61.19 cm x 21.2 cm x 43.34 cm - with stand
Weight	9.71 kg

Connectivity

Interfaces	2 x HDMI (HDCP 2.2) DisplayPort (DisplayPort 1.4 mode) Thunderbolt 3 / USB-C upstream (power up to 90W) Thunderbolt 3 / USB-C downstream (power up to 15W) 2 x USB 3.2 Gen 2 downstream 2 x USB 3.2 Gen 1 downstream with Battery Charging 1.2 Audio line-out
-------------------	---

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	90
Rotation Angle	180
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately), VESA interface support, anti-theft protection
Included Accessories	Shading hood
Cables Included	1 x Thunderbolt 3 / USB-C cable 1 x DisplayPort cable - DisplayPort to DisplayPort SuperSpeed USB-C cable - USB Type A to C 1 x HDMI cable
Compliant Standards	RoHS, BFR-free, DisplayPort 1.4, PVC-free, Mercury-free

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	44 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption Sleep	0.5 Watt
On / Off Switch	No

Software / System Requirements

Included Software	Dell Display Manager, Dell Color Management
--------------------------	---

Dimensions & Weight

Dimensions & Weight Details With stand - width: 61.19 cm - depth: 21.2 cm - height: 43.34 cm - weight: 9.71 kg Without stand - width: 61.19 cm - depth: 5.1 cm - height: 37.68 cm - weight: 5.55 kg

Dimensions & Weight (Shipping)

Shipping Weight 14.14 kg

Environmental Standards

TCO Certified TCO Certified Displays 8

Manufacturer Warranty

Bundled Services 3-Years Advanced Exchange Service and Premium Panel Guarantee

Environmental Parameters

Min Operating Temperature 0 °C

Max Operating Temperature 40 °C

Humidity Range Operating 10 - 90% (non-condensing)