

Produktinformation



Dell E2216HV - LED monitor - Full HD (1080p) - 22"

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	E2216HV

A reliable and affordable monitor with essential features that meet everyday office demands. It features great display quality at multiple angles with VESA-mount compatibility and tilt options, as well as a VGA.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	22"
Viewable Size	21.5"
Panel Type	TN
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.248 mm
Brightness	200 cd/m ²
Contrast Ratio	600:1
Colour Support	16.7 million colours
Response Time	5 ms (black-to-white)
Horizontal Viewing Angle	90
Vertical Viewing Angle	65
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Features	72% (CIE 1931) colour gamut, 85% (CIE 1976) colour gamut, LED light bar system
Colour	Black
Dimensions (WxDxH)	51.22 cm x 18 cm x 39.67 cm - with stand
Weight	3.35 kg

Connectivity	
Interfaces	VGA
Mechanical	
Display Position Adjustments	Tilt
Tilt Angle	-5/+21
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), LED indicator, integrated cable management, VESA interface support, Dell Soundbar mounting slots, arsenic free, mercury free
Cables Included	1 x VGA cable
Compliant Standards	RoHS, CECP
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	18 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption Sleep	0.3 Watt
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 51.22 cm - depth: 18 cm - height: 39.67 cm - weight: 3.35 kg Without stand - width: 51.22 cm - depth: 5.05 cm - height: 30.37 cm - weight: 2.83 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Bundled Services	3 years Advanced Exchange Service
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)