

Produktinformation



Dell EMC PowerEdge T340 - tower - Xeon E-2224 3.4 GHz - 16 GB - HDD 1 TB

Information



<i>Tillverkare</i>	Dell
<i>Artnr</i>	VH1JV

Develop your business with the PowerEdge T340 tower server. It is a reliable, easy to manage, and scalable one-socket server. The PowerEdge T340 helps you share and connect quickly across your organization to drive business results.

Specifikation

General

Type	Server
Bundled Services	3 Years Basic Onsite
Product Form Factor	Tower
Built-in Devices	System health and system ID indicator
Server Scalability	1-way
Hot-Swap Bays Qty	8
Colour	Black

Processor / Chipset

CPU	Intel Xeon E-2224 / 3.4 GHz
Max Turbo Speed	4.6 GHz
Number of Cores	Quad-Core
CPU Qty	1
Max CPU Qty	1
Processor Main Features	Intel Turbo Boost Technology 2

Cache Memory

Installed Size	8 MB
Cache Per Processor	8 MB

RAM

Installed Size	16 GB / 64 GB (max)
Technology	DDR4 SDRAM - ECC
Effective Memory Speed	2666 MHz
Rated Memory Speed	2666 MHz
Form Factor	DIMM 288-pin
Slots	4 (Total) / 3 (empty)
Configuration Features	1 x 16 GB

Hard Drive

Type	HDD - hot-swap
Capacity	1 x 1 TB
Interface Type	SATA
Spindle Speed	7200 rpm

Storage Controller

Type	1 x RAID
Storage Controller Name	Dell PERC H330

Optical Storage

Type	DVD-Writer DVD-Writer
-------------	-----------------------

Monitor

Monitor Type	None.
---------------------	-------

Graphics Controller

Graphics Processor	Matrox G200eR2
Video Memory	16 MB
Video Interfaces	VGA

Networking

Interface (Bus) Type	LAN-on-motherboard (LOM)
Ethernet Ports	2 x Gigabit Ethernet
Ethernet Controller	Broadcom BCM5720
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Controller	Integrated Dell Remote Access Controller 9 Express (iDRAC9)

Expansion / Connectivity

Bays	8 (total) / 7 (free) x hot-swap 3.5"
Slots	1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, full-height (x8 mode) 1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, full-height (x16 mode) 1 (total) / 1 (free) x PCIe 3.0 x1 - half-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x4 - half-length, full-height (x8 mode)
Interfaces	4 x USB 2.0 - Type A 2 x LAN (Gigabit Ethernet) 1 x management (NIC) (iDRAC dedicated port) 2 x VGA (1 front, 1 rear) 1 x serial 3 x USB

3.0 - Type A (1 front, 2 rear) 1 x management - micro-USB (1 in front)
(iDRAC Direct port)

Miscellaneous

Included Accessories	Bezel
Pricing Type	Build To Plan (BTP)

Power

Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	495 Watt
80 PLUS Certification	80 PLUS Platinum

Operating System / Software

OS Provided	No operating system
--------------------	---------------------

Manufacturer Warranty

Service & Support	Limited warranty - 3 years - response time: next business day
------------------------------	---

Dimensions & Weight

Width	30.79 cm
Height	44.33 cm
Weight	25.25 kg

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 80%