

Produktinformation



Information



<i>Tillverkare</i>	Eizo
<i>Artnr</i>	EV2430-BK

EIZO FlexScan EV2430-BK - LED monitor - Full HD (1080p) - 24.1"

In terms of image quality and ergonomics, the EV2430-BK works well when paired with sophisticated computer workstations with the high demands. Antireflection technology and Auto EcoView ensure an anti-glare view of the screen.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	24.1"
Built-in Devices	USB 2.0 hub
Panel Type	IPS
Aspect Ratio	16:10
Native Resolution	Full HD (1080p) 1920 x 1200 at 60 Hz
Pixel Pitch	0.27 mm
Brightness	300 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours (8-bit)
Response Time	14 ms (grey-to-grey)
Vertical Refresh Rate	55 - 61 Hz
Horizontal Refresh Rate	31 - 76 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	LED backlight
OSD Languages	English, German, French, Italian, Spanish, Japanese, Chinese

Features	HDCP, Auto EcoView, The Paper Mode, Flicker Free technology, Transition Minimised Differential Signaling (TMDS) technology, Movie Mode, sRGB Mode
Colour	Black
Dimensions (WxDxH)	55.3 cm x 23.3 cm x 36.8 cm - with stand
Weight	6.7 kg
Audio	
Type	Speakers
Connectivity	
Interfaces	VGA DVI-D (HDCP) DisplayPort (HDCP) Audio line-in Headphones USB 2.0 upstream 2 x USB 2.0 downstream
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	344
Rotation Angle	90
Height Adjustment	140 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Cables Included	1 x DVI cable - DVI-D to DVI-D 1 x DisplayPort cable - DisplayPort to DisplayPort 1 x network cable
Compliant Standards	Plug and Play, FCC Class B certified, TUV GS, DVI DMPM, TUV S, VESA DPMS, CB, ICES-003 Class B, CCC, RoHS, WEEE, cTUVus, VCCI Class B, EAC, RCM, BIS, DisplayPort 1.1a
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	12 Watt
Power Consumption Stand by	0.3 Watt
Software / System Requirements	
Included Software	ScreenManager Pro for LCD, EIZO ScreenSlicer
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 55.3 cm - depth: 5.7 cm - height: 35.8 cm - weight: 4.3 kg With stand - width: 55.3 cm - depth: 23.3 cm - height: 36.8 cm - weight: 6.7 kg
Environmental Standards	
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 5 years