

Produktinformation



Information



Tillverkare Eizo
Artnr EV2460-BK

EIZO FlexScan EV2460 - LED monitor - Full HD (1080p) - 23.8"

The EV2460 uses a 23.8-inch IPS panel with full HD (1920 x 1080) resolution. The small-footprint monitor has a width of just 537.8 mm for saving desk space. Furthermore, 140 mm height adjustment allows you to easily place a laptop under monitor to realize a convenient dual-screen environment.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A++
Energy Consumption per Year	18 kWh
Power Consumption (On mode)	12 W
Diagonal Size	23.8"
Built-in Devices	USB 3.1 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080
Pixel Pitch	0.275 mm
Pixel Per Inch	93
Brightness	250 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	61 Hz
Horizontal Refresh Rate	68 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178

Backlight Technology	LED backlight
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Swedish, Spanish, Japanese
Bezel Type	Flat front
Features	HDCP, Auto EcoView, FlexStand, Flicker Free technology, Movie Mode, sRGB Mode, Low Blue Light Content, Zero Bright Pixels
Colour	Black
Dimensions (WxDxH)	53.78 cm x 23.3 cm x 33.36 cm - with stand
Weight	5.9 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	1 Watt
Connectivity	
Interfaces	VGA DVI-D (HDCP) DisplayPort (HDCP) HDMI (HDCP) Headphones (mini-jack) USB 3.1 upstream (Type B) 4 x USB 3.1 Gen 1 downstream (Type A) Audio line-in (mini-jack)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+35
Swivel Angle	344
Rotation Angle	90
Height Adjustment	140 mm
VESA Mounting Interface	100 x 100 mm, VESA
Miscellaneous	
Included Accessories	Screws
Cables Included	1 x DisplayPort cable - 2 m 2 x USB cable
Compliant Standards	TUV GS, TUV S, CB, CCC, TUV Ergo, RoHS, WEEE, PSE Mark, FCC CFR47 Part 15 B, cTUVus, EPA, VCCI Class B, EAC, China RoHS, RCM, CAN ICES-3 Class B, TUV LBL
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	10 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.5 Watt
On / Off Switch	Yes
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 53.78 cm - depth: 5.36 cm - height: 32.04 cm - weight: 3.8 kg With stand - width: 53.78 cm - depth: 23.3 cm - height: 33.36 cm - weight: 5.9 kg

Environmental Standards

TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes

Manufacturer Warranty

Service & Support	Limited warranty - 5 years
------------------------------	----------------------------

Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)