

## Produktinformation



## Information



*Tillverkare* Eizo  
*Artnr* EV2780-BK

## EIZO FlexScan EV2780-BK - LED monitor - 27"

The generous 27-inch screen is flush with the 1 mm bezels for a completely flat surface from corner to corner. Additionally the internal power unit and USB Type-C connectivity reduces the need for excessive cables.

## Specifikation

### General

<b>Display Type</b>	LED-backlit LCD monitor / TFT active matrix
<b>Energy Class</b>	Class A
<b>Energy Consumption per Year</b>	42 kWh
<b>Power Consumption (On mode)</b>	29 W
<b>Diagonal Size</b>	27"
<b>Built-in Devices</b>	USB 3.1 hub
<b>Panel Type</b>	IPS
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	2560 x 1440
<b>Pixel Pitch</b>	0.233 mm
<b>Brightness</b>	350 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1000:1
<b>Colour Support</b>	16.8 million colours
<b>Response Time</b>	5 ms (grey-to-grey)
<b>Vertical Refresh Rate</b>	29 - 61 Hz
<b>Horizontal Refresh Rate</b>	31 - 89 kHz
<b>Horizontal Viewing Angle</b>	178
<b>Vertical Viewing Angle</b>	178
<b>Backlight Technology</b>	LED backlight

<b>OSD Languages</b>	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Swedish, Spanish, Japanese
<b>Features</b>	Picture by picture, ClearView, HDCP, Auto Brightness Control, FlexStand, Flicker Free technology, blue light reduction, colour adjustment mode, Ultra Slim Design Bezel
<b>Colour</b>	Black
<b>Dimensions (WxDxH)</b>	61.16 cm x 24.5 cm x 39.02 cm - with stand
<b>Weight</b>	8.1 kg
Audio	
<b>Type</b>	Speakers - stereo
<b>Output Power / Channel</b>	1 Watt
Connectivity	
<b>Interfaces</b>	HDMI (HDCP) DisplayPort (HDCP) USB-C downstream (HDCP) 2 x USB 3.1 upstream (Type A) Headphones (mini-jack)
Mechanical	
<b>Display Position Adjustments</b>	Height, pivot (rotation), swivel, tilt
<b>Tilt Angle</b>	-5/+35
<b>Swivel Angle</b>	344
<b>Rotation Angle</b>	180
<b>Height Adjustment</b>	155 mm
<b>VESA Mounting Interface</b>	100 x 100 mm
Miscellaneous	
<b>Features</b>	Volume control
<b>Cables Included</b>	1 x USB-C cable - USB-C
<b>Compliant Standards</b>	FCC Class B certified, TUV GS, DVI DMPM, TUV S, VESA DPMS, CB, CCC, TUV Ergo, RoHS, WEEE, cTUVus, EPA, VCCI Class B, EAC, China RoHS, RCM, CAN ICES-3 Class B, TUV Rheinland, DisplayPort 1.1a
Power	
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	23 Watt
<b>Power Consumption Stand by</b>	0.5 Watt
<b>Power Consumption (Off Mode)</b>	0.5 Watt
Software / System Requirements	
<b>Included Software</b>	EIZO Screen InStyle
Dimensions & Weight	
<b>Dimensions &amp; Weight Details</b>	With stand - width: 61.16 cm - depth: 24.5 cm - height: 39.02 cm - weight: 8.1 kg Without stand - width: 61.16 cm - depth: 4.85 cm - height: 35.9 cm - weight: 5.3 kg

Environmental Standards

**ENERGY STAR Certified** Yes

Manufacturer Warranty

**Service & Support** Limited warranty - 5 years

Environmental Parameters

**Min Operating Temperature** 5 °C

**Max Operating Temperature** 35 °C

**Humidity Range Operating** 20 - 80% (non-condensing)