

## Produktinformation



## Information



Tillverkare

Eizo

Artnr

FDF2382WT-BK

## EIZO DuraVision FDF2382WT - LED monitor - Full HD (1080p) - 23"

The DuraVision FDF2382WT features projected capacitive touch technology which is more durable and reliable compared to other touch technologies. The monitor accepts touch input from a bare finger or dedicated stylus.

## Specifikation

### General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	23"
Built-in Devices	USB 2.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.265 mm
Brightness	260 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Colour Support	16.7 million colours (8-bit)
Response Time	11 ms (grey-to-grey)
Vertical Refresh Rate	55 - 76 Hz
Horizontal Refresh Rate	31 - 81 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 5H Hard Coating
Backlight Technology	LED backlight
Colour Temperature	10000K, 4000K
OSD Languages	English, German, French, Italian, Swedish, Spanish, Japanese, Chinese

<b>Features</b>	HDCP, Overdrive technology, frameless, tempered glass, scratch-resistant, 10-bit lookup table, Projected Capacitive Touch (P-CAP) technology, Transition Minimised Differential Signaling (TMDS) technology, sRGB Color Space, Colour Temperature Selection, tilt stand
<b>Colour</b>	Black
<b>Dimensions (WxDxH)</b>	55.67 cm x 14.49 cm x 21.63 cm - with stand
<b>Weight</b>	7 kg
Audio	
<b>Type</b>	Speakers - stereo
<b>Output Power / Channel</b>	1 Watt
Input	
<b>Type</b>	Touch-screen - touchscreen
<b>Movement Detection Technology</b>	Projected capacitive
<b>Touchscreen Life</b>	50 million touches
Connectivity	
<b>Interfaces</b>	DisplayPort (HDCP) DVI-D (HDCP) VGA Audio line-in Audio line-out USB 2.0 upstream (Type B) 2 x USB 2.0 downstream (Type A)
Mechanical	
<b>Display Position Adjustments</b>	Pivot (rotation), tilt
<b>Tilt Angle</b>	15/+70
<b>Rotation Angle</b>	17
<b>VESA Mounting Interface</b>	100 x 100 mm
Miscellaneous	
<b>Included Accessories</b>	Cleaning cloth, cover
<b>Cables Included</b>	1 x network cable 1 x DisplayPort cable 1 x DVI cable 1 x USB cable 1 x audio cable
<b>Compliant Standards</b>	FCC Class B certified, C-Tick, DVI DMPM, TUV S, VESA DPMS, CB, CCC, RoHS, WEEE, GOST-R, cTUVus, VCCI Class B, CAN ICES-3 Class B
Power	
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	14 Watt
<b>Power Consumption Stand by</b>	0.7 Watt
<b>Power Consumption (Off Mode)</b>	0 Watt
Software / System Requirements	
<b>Included Software</b>	Drivers & Utilities
<b>OS Required</b>	Microsoft Windows 7 (32/64 bits), Windows 8.1 (32/64 bits), Windows 10 (32/64 bits)

Dimensions & Weight

**Dimensions & Weight Details** With stand - width: 55.67 cm - depth: 14.49 cm - height: 21.63 cm - weight: 7 kg Without stand - width: 55.67 cm - depth: 5.4 cm - height: 33.92 cm - weight: 6 kg

Manufacturer Warranty

**Service & Support** Limited warranty - replacement - 3 years - on-site

Environmental Parameters

**Min Operating Temperature** 5 °C  
**Max Operating Temperature** 35 °C  
**Humidity Range Operating** 20 - 80% (non-condensing)