

## Produktinformation



### Information



*Tillverkare* Eizo  
*Artnr* S2133-BK

## EIZO FlexScan S2133-BK - LED monitor - 21.3"

With its IPS panel and 1600 x 1200, resolution, the FlexScan S2133 is ideal for businesses and control rooms that need to display a large volume of data as well as for CAD and other design work that require brilliant color display.

## Specifikation

### General

<b>Display Type</b>	LED-backlit LCD monitor / TFT active matrix
<b>Diagonal Size</b>	21.3"
<b>Built-in Devices</b>	USB 2.0 hub
<b>Panel Type</b>	IPS
<b>Aspect Ratio</b>	4:3
<b>Native Resolution</b>	1600 x 1200
<b>Pixel Pitch</b>	0.27 mm
<b>Brightness</b>	420 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1500:1
<b>Colour Support</b>	16.8 million colours
<b>Response Time</b>	6 ms (grey-to-grey)
<b>Vertical Refresh Rate</b>	49 - 76 Hz
<b>Horizontal Refresh Rate</b>	24 - 80 kHz
<b>Video Bandwidth</b>	162 MHz
<b>Horizontal Viewing Angle</b>	178
<b>Vertical Viewing Angle</b>	178
<b>Screen Coating</b>	Anti-glare
<b>Backlight Technology</b>	LED backlight
<b>Controls &amp; Adjustments</b>	Brightness, contrast, H/V position, saturation, gamma correction, colour temperature, phase, clock, H-size

<b>OSD Languages</b>	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Swedish, Spanish, Japanese
<b>Features</b>	sRGB colour management, Fine Contrast, Auto EcoView, 10-bit gamma, Composite Sync
<b>Colour</b>	Black
<b>Dimensions (WxDxH)</b>	46.5 cm x 20.85 cm x 45.3 cm - with stand
<b>Weight</b>	8.6 kg
Connectivity	
<b>Interfaces</b>	VGA DVI-D (HDCP) DisplayPort (HDCP) USB 2.0 upstream (Type B) 2 x USB 2.0 downstream (Type A)
Mechanical	
<b>Display Position Adjustments</b>	Height, pivot (rotation), swivel, tilt
<b>Tilt Angle</b>	40
<b>Swivel Angle</b>	70
<b>Rotation Angle</b>	90
<b>Height Adjustment</b>	82 mm
<b>VESA Mounting Interface</b>	100 x 100 mm
Miscellaneous	
<b>Features</b>	Security lock slot (cable lock sold separately)
<b>Cables Included</b>	1 x DVI cable - DVI-D to DVI-D - 2 m 1 x VGA cable - 1.8 m 1 x USB cable - 1.8 m
<b>Compliant Standards</b>	FCC Class B certified, TUV GS, TUV S, CB, CCC, TUV Ergo, DDC/CI, RoHS, WEEE, cTUVus, VCCI Class B, EAC, China RoHS, RCM, CAN ICES-3 Class B, TUV Rheinland, HDCP 1.3, HDCP 1.4
<b>Security Slot Type</b>	Kensington security slot
Power	
<b>Power Supply</b>	Internal
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	13 Watt
<b>Power Consumption Stand by</b>	0.3 Watt
Software / System Requirements	
<b>Included Software</b>	Drivers & Utilities, EIZO ScreenSlicer, ScreenManager Pro for DDC
Dimensions & Weight	
<b>Dimensions &amp; Weight Details</b>	With stand - width: 46.5 cm - depth: 20.85 cm - height: 45.3 cm - weight: 8.6 kg Without stand - width: 46.5 cm - depth: 6.4 cm - height: 36.1 cm - weight: 5.6 kg
Environmental Standards	
<b>ENERGY STAR Certified</b>	Yes

Manufacturer Warranty

**Service & Support**

Limited warranty - 5 years

Environmental Parameters

**Min Operating Temperature**

5 °C

**Max Operating Temperature**

35 °C

**Humidity Range Operating**

20 - 80% (non-condensing)