

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E107766

Elo Desktop Touchmonitors 2201L IntelliTouch Plus - LED monitor - Full HD (1080p) - 22"

The 2201L offers a flexible, space-saving design, HD wide-aspect ratio 22-inch LCD touch monitor. Well-suited to meet durability as well as aesthetic requirements for front-of-store, back office, kiosk and even out-of-store applications, the Elo Touch Solutions 2201L offers real versatility for a variety of retail and hospitality interactive solutions. The 2201L with Intellitouch plus multi-touch surface acoustic wave (SAW) touchscreen technology provides stable "drift-free" operation with outstanding image clarity, resolution, and light transmission - for an accurate touch response. Wide-screen format displays allow extra content on the screen and are quickly becoming preferred in corporate environments for publishing and dual window applications, and are popular in public venue environments due to a high-definition cinematic-like experience.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	22"
Built-in Devices	Stereo speakers
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Brightness	225 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	5 ms
Vertical Refresh Rate	75 Hz
Horizontal Refresh Rate	80 kHz
Horizontal Viewing Angle	170
Vertical Viewing Angle	160
Backlight Technology	LED backlight

Controls & Adjustments	Mute, volume, brightness, contrast, H/V position, sharpness, colour temperature, phase, clock, aspect control
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	IntelliTouch Plus Surface Acoustic Wave
Colour	Black
Dimensions (WxDxH)	55.1 cm x 19.3 cm x 39.2 cm - with stand
Weight	7.5 kg
Audio	
Type	Speakers - stereo - internal
Output Power / Channel	2 Watt
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Intellitouch SAW
Connectivity	
Interfaces	DVI-D VGA Audio line-in USB Headphones
Mechanical	
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately)
Backlight Life	30,000 hours
MTBF	50,000 hour(s)
Compliant Standards	UL, VCCI, C-Tick, BSMI, GOST, cUL, NOM, CB, CCC, IC, FCC, RoHS, KCC, WEEE
Localisation	Worldwide
Power	
Power Supply	External
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	29 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)