

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E125695

Elo 1902L - LED monitor - 19"

The Elo 1902L 19-inch touchscreen monitor delivers a professional-grade interactive solution with Elo's industry-leading TouchPro PCAP technology featuring edge-to-edge glass and enabling up to 10 simultaneous touches. The clear glass touchscreen provides exceptional image clarity, resolution, and light transmission for vivid images and details. The feature rich touchscreen monitor is equipped with dual built-in speakers and VGA and HDMI video connectors. With a compact form factor, clean design aesthetic and flexible mounting options, these touchscreens are well-suited for POS, interactive digital signage and self-service.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	19"
Built-in Devices	USB Hub
Aspect Ratio	5:4
Native Resolution	1280 x 1024 at 60 Hz
Brightness	250 cd/m ²
Brightness w/touchscreen	225 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	14 ms (tr - tf)
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 82 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Backlight Technology	LED backlight
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Russian, Spanish, Japanese, Korean
Features	TouchPro technology

Colour	Black
Dimensions (WxDxH)	42.96 cm x 4.16 cm x 35.46 cm - without stand
Weight	4.3 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	2 Watt
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
Connectivity	
Interfaces	HDMI VGA Headphones USB (Type B) USB 2.0 (Type A) 4 x Micro-USB
Mechanical	
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Included Accessories	3 cable ties, screws
Cables Included	1 x VGA cable 1 x HDMI cable 1 x USB cable 1 x audio cable
MTBF	50,000 hours
Compliant Standards	UL, VCCI, BSMI, cUL, CB, CCC, IC, FCC, KCC, IPX1, EAC, RCM, CoC
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	18 Watt
Power Consumption Sleep	0.8 Watt
Dimensions & Weight (Shipping)	
Shipping Width	48.2 cm
Shipping Depth	19 cm
Shipping Height	52.7 cm
Shipping Weight	6.5 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)