

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E155645

Elo 1502L - M-Series - LED monitor - Full HD (1080p) - 15.6"

The Elo 1502L 15.6-inch touchscreen monitor delivers a professional-grade interactive solution featuring Elo's industry-leading TouchPro PCAP technology with edge-to-edge glass enabling up to 10 simultaneous touches. The feature rich monitor offers a sleek, low-profile, commercial-ready solution with dual built-in speakers and USB Type B or C (depending on the model), VGA and HDMI video connectors. With a compact form factor and flexible mounting options, the 1502L is well-suited for POS, self-service, signage and customer-facing point of interaction. Designed for commercial use, the 1502L simplifies business operations by delivering energy efficiency and versatile accessory options - from EMV and MSR payment devices to a barcode scanner and customer facing display.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	15.6"
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Brightness	300 cd/m ²
Brightness w/touchscreen	270 cd/m ²
Contrast Ratio	700:1
Colour Support	16.7 million colours
Response Time	35 ms
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	31.5 - 82 kHz
Horizontal Viewing Angle	+80 / -80
Vertical Viewing Angle	+80 / -80
Screen Coating	Anti-glare
Backlight Technology	LED backlight

OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	Edge-to-edge glass, Zero-Bezel Design, Projected Capacitive Touch (P-CAP) technology
Colour	Black
Dimensions (WxDxH)	38.7 cm x 19.91 cm x 28.5 cm - with stand
Weight	3.05 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	2 Watt
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
Connectivity	
Interfaces	Mini-VGA HDMI USB (Type C) Audio line-in 3 x Micro-USB
Mechanical	
VESA Mounting Interface	100 x 100 mm, 75 x 75 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), VESA interface support
Included Accessories	3 screws, 2 screws, cable clamp, 2 tie wraps
Cables Included	1 x HDMI cable 1 x USB-A to USB-C adapter
MTBF	50,000 hour(s)
Compliant Standards	UL, VCCI, BSMI, cUL, NOM, CB, CCC, IC, FCC, RoHS, KCC, WEEE, REACH, E-Standby, IPX1, RCM, BIS
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	12 Watt
Power Consumption Sleep	2 Watt
Power Consumption (Off Mode)	0.2 Watt
Dimensions & Weight (Shipping)	
Shipping Width	20.4 cm
Shipping Depth	45.1 cm
Shipping Height	34.4 cm
Shipping Weight	5.01 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)