

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E266835

Elo 1915L IntelliTouch - LED monitor - 19"

The 1915L touchmonitor is designed, developed and built to provide the most cost-effective touch solutions for system integrators and VARs. It packs Elo quality and reliability into an integrated, affordable touchmonitor. This compact touchmonitor is "designed for touch" from the ground up, with Elo expertise and reliability built in. The 1915L desktop touchmonitor with Elo's IntelliTouch surface acoustic wave technology has a dual serial/USB touch interface, offers pure glass image quality and continues to function even if scratched.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	19"
Native Resolution	1280 x 1024 at 75 Hz
Brightness	225 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	5 ms
Vertical Refresh Rate	56.3 - 75 Hz
Horizontal Refresh Rate	31.5 - 80 kHz
Horizontal Viewing Angle	+85 / -85
Vertical Viewing Angle	+80 / -80
Backlight Technology	LED backlight
Controls & Adjustments	Brightness, contrast, H/V position, colour temperature, phase, clock
OSD Languages	English, German, French, Spanish, Japanese
Features	IntelliTouch Surface Wave, anti-glare, OSD lock
Colour	Dark grey
Dimensions (WxDxH)	42.9 cm x 20.7 cm x 37.9 cm
Weight	7.9 kg

Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Intellitouch SAW
Connectivity	
Interfaces	VGA Serial USB
Interfaces	1 x VGA - 15 pin HD D-Sub (HD-15) 1 x serial RS-232 - 9 pin D-Sub (DB-9) 1 x USB - 4 pin USB Type A
Mechanical	
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Water-resistant, wall mountable, dust-resistant, dirt resistant, Flexible Mounting Profile, mounting holes, security lock
Cables Included	1 x VGA cable - 1.8 m 1 x USB cable - USB Type A to B - 1.83 m
MTBF	50,000 hour(s)
Compliant Standards	FCC Class B certified, IC Class B, UL, TUV GS, VCCI Class B ITE, cUL, C-Tick Class B, RoHS
Localisation	EMEA, Americas
Power	
Power Supply	Internal
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	23 Watt
Power Consumption Sleep	1.19 Watt
Power Consumption (Off Mode)	0.63 Watt
Dimensions & Weight (Shipping)	
Shipping Width	54 cm
Shipping Depth	28.5 cm
Shipping Height	49.5 cm
Shipping Weight	11.7 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80%