

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E273226

Elo 1517L iTouch Zero-Bezel - LED monitor - 15"

The Elo 1517L 15-inch standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look coupled with a retail-focused feature set makes it an attractive solution for commercial touchscreen monitor needs. With an optional, easy to install 3-track magnetic stripe reader (MSR), the 1517L provides an elegant, integrated solution, eliminating the need for external brackets or attachments. The 1517L, offered in white or black, is well suited for point-of-sale, point-of-information, point-of-service, interactive signage and loyalty systems. The touchscreen monitor offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. The 1517L touch monitor is environmentally friendly and lightweight, using less power with state-of-the-art LED backlights in the display panel.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	15"
Aspect Ratio	4:3
Native Resolution	1024 x 768 at 75 Hz
Brightness	300 cd/m ²
Brightness w/touchscreen	270 cd/m ²
Contrast Ratio	800:1
Colour Support	16.2 million colours
Response Time	23 ms
Horizontal Viewing Angle	+80 / -80
Vertical Viewing Angle	+70 / -70
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Controls & Adjustments	Brightness, contrast, H/V position, sharpness, colour balance, colour temperature, phase, clock, aspect control

OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	IntelliTouch ZB Surface Acoustic Wave (SAW)
Colour	Black
Dimensions (WxDxH)	35.8 cm x 19.7 cm x 31.9 cm - with stand
Weight	4.3 kg
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Intellitouch SAW
Connectivity	
Interfaces	Serial USB VGA
Mechanical	
VESA Mounting Interface	75 x 75 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately)
MTBF	50,000 hour(s)
Compliant Standards	UL, VCCI, C-Tick, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, S Mark, China RoHS
Localisation	Worldwide
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	10.5 Watt
Power Consumption Stand by	0.92 Watt
Power Consumption Sleep	0.5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)