

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E328497

Elo Open-Frame Touchmonitors 1990L - LED monitor - 19"

The Elo 1990L 19-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions due to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch, with proven Elo expertise and reliability built in. The 1990L provides stable, drift-free operation with outstanding image clarity and light transmission - for accurate touch responses and vivid images. Instantly grabbing and holding users' attention, the open-frame touchscreen is perfect for kiosks, casino and amusement, retail self-service, and industrial automation environments.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class B
Energy Consumption per Year	34 kWh
Power Consumption (On mode)	23 W
Diagonal Size	19"
Aspect Ratio	5:4
Native Resolution	1280 x 1024 at 60 Hz
Brightness	250 cd/m ²
Brightness w/touchscreen	225 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	5 ms
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 82 kHz
Horizontal Viewing Angle	+85 / -85
Vertical Viewing Angle	+80 / -80
Backlight Technology	LED backlight

OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	Remote OSD, Slim Design, IntelliTouch Surface Acoustic Wave
Colour	Black
Dimensions (WxDxH)	41.47 cm x 5 cm x 34.27 cm
Weight	4.6 kg
Input	
Type	Touchscreen
Connectivity	
Interfaces	USB VGA DisplayPort HDMI Serial
Mechanical	
VESA Mounting Interface	100 x 100 mm, 75 x 75 mm
Miscellaneous	
Cables Included	1 x USB cable 1 x VGA cable 1 x HDMI cable
Mounting Kit	Included
MTBF	50,000 hours
Compliant Standards	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, DisplayPort 1.1a, IMERC
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	22 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)