

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E328883

Elo 2094L - LED monitor - Full HD (1080p) - 19.53"

The Elo 2094L 19.5-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions due to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch, with proven Elo expertise and reliability built in. The 2094L provides stable, drift-free operation with outstanding image clarity and light transmission - for accurate touch responses and vivid images. Featuring a brilliant wide viewing angle panel, the open-frame touchscreen instantly grabs and holds the users' attention for kiosks, casino and amusement, retail self-service, and industrial automation environments.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class B
Energy Consumption per Year	29 kWh
Power Consumption (On mode)	20 W
Diagonal Size	19.53"
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Brightness	250 cd/m ²
Brightness w/touchscreen	225 cd/m ²
Contrast Ratio	3000:1
Colour Support	16.7 million colours
Response Time	20 ms
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 82 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Backlight Technology	LED backlight

OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	Remote OSD, IntelliTouch Surface Acoustic Wave
Colour	Black
Dimensions (WxDxH)	47.6 cm x 4.34 cm x 28.01 cm
Weight	4.7 kg
Input	
Type	Touch-screen, remote control - touchscreen
Movement Detection Technology	Intellitouch SAW
Connectivity	
Interfaces	USB VGA DisplayPort HDMI Serial
Mechanical	
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Cables Included	1 x USB cable 1 x VGA cable 1 x HDMI cable
Mounting Kit	Included
MTBF	50,000 hours
Compliant Standards	UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, DisplayPort 1.1a, IMERC
Power	
Power Consumption Operational	17.6 Watt
Power Consumption Sleep	1.5 Watt
Power Consumption (Off Mode)	0.5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)