

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E331214

Elo 2094L - LED monitor - Full HD (1080p) - 19.53"

The Elo 2094L 19.5-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions due to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch, with proven Elo expertise and reliability built in. The 2094L provides stable, drift-free operation with outstanding image clarity and light transmission - for accurate touch responses and vivid images. Featuring a brilliant wide viewing angle panel, the open-frame touchscreen instantly grabs and holds the users' attention for kiosks, casino and amusement, retail self-service, and industrial automation environments.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class B
Energy Consumption per Year	29 kWh
Power Consumption (On mode)	20 W
Diagonal Size	19.53"
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Brightness	250 cd/m ²
Brightness w/touchscreen	225 cd/m ²
Contrast Ratio	3000:1
Colour Support	16.7 million colours
Response Time	20 ms
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 82 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Backlight Technology	LED backlight

OSD Languages Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese

Features Remote OSD, Projected Capacitive Touch (P-CAP) technology

Colour Black

Dimensions (WxDxH) 47.9 cm x 4.04 cm x 28.5 cm

Weight 4.7 kg

Input

Type Touch-screen, remote control - touchscreen

Movement Detection Technology Projected capacitive

Connectivity

Interfaces USB VGA DisplayPort HDMI

Mechanical

VESA Mounting Interface 100 x 100 mm

Miscellaneous

Cables Included 1 x USB cable 1 x VGA cable 1 x HDMI cable

Mounting Kit Included

MTBF 50,000 hours

Compliant Standards UL, TUV, VCCI, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, China RoHS, RCM, CoC, DisplayPort 1.1a, IMERC

Power

Power Consumption Operational 17.6 Watt

Power Consumption Sleep 1.5 Watt

Power Consumption (Off Mode) 0.5 Watt

Manufacturer Warranty

Service & Support Limited warranty - 3 years

Environmental Parameters

Min Operating Temperature 0 °C

Max Operating Temperature 40 °C

Humidity Range Operating 20 - 80% (non-condensing)