

## Produktinformation



### Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E351388

## Elo 1902L - LCD monitor - 19"

The Elo 1902L 19-inch touchscreen monitor delivers a professional-grade interactive solution with Elo's industry-leading TouchPro PCAP technology featuring edge-to-edge glass and enabling up to 10 simultaneous touches. The clear glass touchscreen provides exceptional image clarity, resolution, and light transmission for vivid images and details. The feature rich touchscreen monitor is equipped with dual built-in speakers and VGA and HDMI video connectors. With a compact form factor, clean design aesthetic and flexible mounting options, these touchscreens are well-suited for POS, interactive digital signage and self-service.

## Specifikation

### General

<b>Display Type</b>	LCD monitor / TFT active matrix
<b>Diagonal Size</b>	19"
<b>Built-in Devices</b>	USB Hub
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 at 60 Hz
<b>Brightness</b>	250 cd/m <sup>2</sup>
<b>Brightness w/touchscreen</b>	235 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1000:1
<b>Colour Support</b>	16.7 million colours
<b>Response Time</b>	14 ms (tr - tf)
<b>Vertical Refresh Rate</b>	50 - 75 Hz
<b>Horizontal Refresh Rate</b>	30 - 82 kHz
<b>Horizontal Viewing Angle</b>	+89 / -89
<b>Vertical Viewing Angle</b>	+89 / -89
<b>OSD Languages</b>	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Russian, Spanish, Japanese, Korean
<b>Features</b>	TouchPro technology
<b>Colour</b>	Black

<b>Dimensions (WxDxH)</b>	42.96 cm x 19.34 cm x 39.77 cm - with stand
<b>Weight</b>	6.3 kg
Audio	
<b>Type</b>	Speakers - stereo
<b>Output Power / Channel</b>	2 Watt
Input	
<b>Type</b>	Touch-screen - touchscreen
<b>Movement Detection Technology</b>	Projected capacitive
Connectivity	
<b>Interfaces</b>	HDMI VGA Headphones USB (Type B) USB 2.0 (Type A) 4 x Micro-USB
Mechanical	
<b>VESA Mounting Interface</b>	100 x 100 mm
Miscellaneous	
<b>Included Accessories</b>	3 cable ties
<b>Cables Included</b>	1 x VGA cable 1 x HDMI cable 1 x USB cable 1 x audio cable
<b>MTBF</b>	50,000 hours
<b>Compliant Standards</b>	UL, VCCI, BSMI, cUL, CB, CCC, IC, FCC, KCC, IPX1, EAC, RCM, CoC
Power	
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	18 Watt
<b>Power Consumption Sleep</b>	0.8 Watt
Dimensions & Weight (Shipping)	
<b>Shipping Width</b>	48.2 cm
<b>Shipping Depth</b>	26 cm
<b>Shipping Height</b>	52.7 cm
<b>Shipping Weight</b>	9.8 kg
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 3 years
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	20 - 80% (non-condensing)