

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E534869

Elo 1509L - LED monitor - 15.6"

The Elo 1509L 15.6-inch widescreen LED touchscreen monitor delivers a low-profile, retail-hardened solution with a pure glass construction to allow high light transmission without compromising durability or functionality. Available with IntelliTouch surface acoustic wave (SAW) offering single touch capacity, the 1509 has been "built for touch" offering an ideal solution for general applications including hospitality and retail environments. The touchscreen monitor can be affixed to a counter, or when the stand is removed, mounted on a wall or to a pole, and with the LED backlight power consumption is significantly reduced. The low profile wide-screen display provides additional on-screen space for extra sidebar menus, on-screen keypads or additional modules in the application. The 1509L also helps improve customer interaction by allowing the employee to maintain visibility with the customer.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	15.6"
Aspect Ratio	16:9
Native Resolution	1366 x 768 at 60 Hz
Brightness	220 cd/m ²
Brightness w/touchscreen	198 cd/m ²
Contrast Ratio	300:1
Colour Support	16.7 million colours
Response Time	16 ms
Vertical Refresh Rate	60 Hz
Horizontal Refresh Rate	30 - 80 kHz
Horizontal Viewing Angle	+40 / -40
Vertical Viewing Angle	+10 / -30
Backlight Technology	LED backlight
Controls & Adjustments	Brightness, contrast, H/V position, sharpness, colour temperature, phase, clock

OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	IntelliTouch Surface Wave
Colour	Black
Dimensions (WxDxH)	39.2 cm x 22.8 cm x 28.5 cm - with stand
Weight	2.4 kg
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Surface acoustic wave
Connectivity	
Interfaces	VGA
Mechanical	
VESA Mounting Interface	75 x 75 mm
Miscellaneous	
Features	IntelliTouch Surface Wave
Included Accessories	Stand
MTBF	50,000 hour(s)
Compliant Standards	UL, VCCI, C-Tick, BSMI, GOST, cUL, SABs, SASO, CB, CCC, IC, FCC, RoHS, KCC, WEEE, SONCAP, KEBS
Localisation	Asia, Latin America, EMEA
Power	
Power Supply	External
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	8 Watt
Power Consumption Sleep	1.8 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)