

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E628053

Elo 5553L - LED monitor - 4K - 55"

Elo's 5553L 55-inch 4K touchscreen display makes it easy to add interactivity to any environment. Perfect for everything from endless aisle and brand experiences to collaborative meetings, conferencing and whiteboarding, the 5553L offers a sleek, slim design built to withstand the rigors of continuous commercial use. And, the added flexibility of integrating an optional computer module turns the display into a powerful 55-inch all-in-one life-size tablet. Available with Elo's industry leading TouchPro Projected Capacitive (PCAP) enabling up to 40 touches or Infrared (IR) touch technology with up to 20 touches, the professional-grade large format display is designed to help you create engaging experiences.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A+
Diagonal Size	55"
Aspect Ratio	16:9
Native Resolution	4K 3840 x 2160 at 60 Hz
Brightness	500 cd/m ²
Brightness w/touchscreen	430 cd/m ²
Contrast Ratio	1100:1
Colour Support	1.07 billion colours
Response Time	8 ms (typical)
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Backlight Technology	LED backlight
Bezel Type	Flat front
Features	Anti-glare, TouchPro Pro Projected Capacitive (PCAP) technology
Colour	Grey

Input

Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
Connectivity	
Interfaces	VGA HDMI USB (Type B) Management (RJ-45)
Mechanical	
VESA Mounting Interface	400 x 400 mm, 600 x 600 mm
Miscellaneous	
Cables Included	1 x HDMI cable
Mounting Kit	Included
MTBF	50,000 hour(s)
Compliant Standards	UL, VCCI, C-Tick, BSMI, cUL, UL 60950, CB, CCC, IC, FCC, RoHS, KCC, WEEE, S Mark, E-Standby, KC, China RoHS, CoC, IK06
Power	
Voltage Required	AC 100 - 240 V (50/60 Hz)
Power Consumption Operational	83.8 Watt
Power Consumption Stand by	1.2 Watt
Power Consumption (Off Mode)	0.37 Watt
Dimensions & Weight (Shipping)	
Shipping Width	141 cm
Shipping Depth	93 cm
Shipping Height	24.4 cm
Environmental Standards	
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)