

## Produktinformation



### Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E628244

## Elo 5553L - LED monitor - 4K - 55"

Elo's 5553L 55-inch 4K touchscreen display makes it easy to add interactivity to any environment. Perfect for everything from endless aisle and brand experiences to collaborative meetings, conferencing and whiteboarding, the 5553L offers a sleek, slim design built to withstand the rigors of continuous commercial use. And, the added flexibility of integrating an optional computer module turns the display into a powerful 55-inch all-in-one life-size tablet. Available with Elo's industry leading TouchPro Projected Capacitive (PCAP) enabling up to 40 touches or Infrared (IR) touch technology with up to 20 touches, the professional-grade large format display is designed to help you create engaging experiences.

## Specifikation

### General

<b>Display Type</b>	LED-backlit LCD monitor / TFT active matrix
<b>Energy Class</b>	Class A+
<b>Diagonal Size</b>	55"
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	4K 3840 x 2160 at 60 Hz
<b>Brightness</b>	500 cd/m <sup>2</sup>
<b>Brightness w/touchscreen</b>	430 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1100:1
<b>Colour Support</b>	1.07 billion colours
<b>Response Time</b>	8 ms (typical)
<b>Horizontal Viewing Angle</b>	+89 / -89
<b>Vertical Viewing Angle</b>	+89 / -89
<b>Backlight Technology</b>	LED backlight
<b>Bezel Type</b>	Flat front
<b>Features</b>	Anti-glare, infrared touch technology
<b>Colour</b>	Grey

### Input

<b>Type</b>	Touch-screen - touchscreen
<b>Movement Detection Technology</b>	Projected capacitive
Connectivity	
<b>Interfaces</b>	VGA HDMI USB (Type B) Management (RJ-45)
Mechanical	
<b>VESA Mounting Interface</b>	400 x 400 mm, 600 x 600 mm
Miscellaneous	
<b>Cables Included</b>	1 x HDMI cable
<b>Mounting Kit</b>	Included
<b>MTBF</b>	50,000 hour(s)
<b>Compliant Standards</b>	UL, VCCI, C-Tick, BSMI, cUL, UL 60950, CB, CCC, IC, FCC, RoHS, KCC, WEEE, S Mark, E-Standby, KC, China RoHS, CoC, IK06
Power	
<b>Voltage Required</b>	AC 100 - 240 V (50/60 Hz)
<b>Power Consumption Operational</b>	83.8 Watt
<b>Power Consumption Stand by</b>	1.2 Watt
<b>Power Consumption (Off Mode)</b>	0.37 Watt
Dimensions & Weight (Shipping)	
<b>Shipping Width</b>	141 cm
<b>Shipping Depth</b>	93 cm
<b>Shipping Height</b>	24.4 cm
Environmental Standards	
<b>ENERGY STAR Certified</b>	Yes
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 3 years
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	20 - 80% (non-condensing)