

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E683457

Elo 1723L - LED monitor - 17"

The Elo touch solutions 1723L 17-inch touch monitor is well-suited to meet the durability and aesthetic requirements for a variety of high traffic retail and hospitality interactive solutions and includes options for 3-track Magnetic Stripe Reader (MSR), webcam, RFID reader and brackets for mounting a 0700L rear facing customer display. iTouch Plus zero-bezel multi-touch surface acoustic wave touchscreen technology provides stable "drift-free" operation with outstanding image clarity, resolution, and light transmission-for an accurate touch response and vivid images. iTouch Plus offers a unique, aesthetically-pleasing seamless design and is resistant to water, impacts, scratches and other contaminants on the screen. The 1723L has been "designed for touch" from the ground up, with such features as a spill-resistant sealing, adjustable height stand with tilting functionality, VESA mounting option, connectivity incorporated within the monitor, and communication cables and side controls with lockout capability.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	17"
Aspect Ratio	5:4
Native Resolution	1280 x 1024 at 75 Hz
Brightness	250 cd/m ²
Brightness w/touchscreen	215 cd/m ²
Contrast Ratio	800:1
Colour Support	16.7 million colours
Response Time	30 ms
Vertical Refresh Rate	56 - 75 Hz
Horizontal Refresh Rate	31 - 80 KHz
Horizontal Viewing Angle	170
Vertical Viewing Angle	160
Backlight Technology	LED backlight
Controls & Adjustments	Mute, volume, brightness, contrast, H/V position, sharpness, colour temperature, phase, clock, aspect control

OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	Anti-glare, IntelliTouch Pro
Colour	Black
Dimensions (WxDxH)	39.19 cm x 20.94 cm x 36.07 cm - with stand
Weight	5.21 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	2 Watt
Input	
Type	Touch-screen - touchscreen
Movement Detection Technology	Projected capacitive
Connectivity	
Interfaces	VGA DVI-D 2 x USB (Type A) USB (Type B)
Mechanical	
Display Position Adjustments	Height, tilt
Tilt Angle	-5/+90
VESA Mounting Interface	75 x 75 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately)
MTBF	50,000 hour(s)
Compliant Standards	Plug and Play, UL, VCCI, C-Tick, BSMI, cUL, VESA DPMS, CB, CCC, IC, FCC, RoHS, DDC, KCC, WEEE, E-Standby, China RoHS, CoC
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	22 Watt
Power Consumption Sleep	2 Watt
Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 39.19 cm - depth: 4.95 cm - height: 32.72 cm - weight: 3.56 kg With stand - width: 39.19 cm - depth: 20.94 cm - height: 36.07 cm - weight: 5.21 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)