

## Produktinformation



### Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E785229

## Elo Desktop Touchmonitors 1723L iTouch Plus - LED monitor - 17"

The Elo touch solutions 1723L 17-inch touch monitor is well-suited to meet the durability and aesthetic requirements for a variety of high traffic retail and hospitality interactive solutions and includes options for 3-track Magnetic Stripe Reader (MSR), webcam, RFID reader and brackets for mounting a 0700L rear facing customer display. iTouch Plus zero-bezel multi-touch surface acoustic wave (SAW) touchscreen technology provides stable "drift-free" operation with outstanding image clarity, resolution, and light transmission-for an accurate touch response and vivid images. iTouch Plus offers a unique, aesthetically-pleasing seamless design and is resistant to water, impacts, scratches and other contaminants on the screen. The 1723L has been "designed for touch" from the ground up, with such features as a spill-resistant sealing, adjustable height stand with tilting functionality, VESA mounting option, connectivity incorporated within the monitor, and communication cables and side controls with lockout capability.

## Specifikation

### General

<b>Display Type</b>	LED-backlit LCD monitor / TFT active matrix
<b>Diagonal Size</b>	17"
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 at 75 Hz
<b>Brightness</b>	225 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	800:1
<b>Colour Support</b>	16.7 million colours
<b>Response Time</b>	30 ms
<b>Vertical Refresh Rate</b>	56 - 75 Hz
<b>Horizontal Refresh Rate</b>	31 - 80 KHz
<b>Horizontal Viewing Angle</b>	170
<b>Vertical Viewing Angle</b>	160
<b>Screen Coating</b>	Anti-glare
<b>Backlight Technology</b>	LED backlight

<b>Controls &amp; Adjustments</b>	Mute, volume, brightness, contrast, H/V position, sharpness, colour temperature, phase, clock, aspect control
<b>OSD Languages</b>	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
<b>Features</b>	OSD lock
<b>Colour</b>	Black
<b>Dimensions (WxDxH)</b>	39.1 cm x 20.9 cm x 36 cm - with stand
<b>Weight</b>	5.21 kg
Audio	
<b>Type</b>	Speakers - stereo - internal
Input	
<b>Type</b>	Touchscreen
Connectivity	
<b>Interfaces</b>	VGA DVI-D 2 x USB (Type A) USB (Type B) Audio line-in
Mechanical	
<b>Display Position Adjustments</b>	Tilt
<b>VESA Mounting Interface</b>	75 x 75 mm
Miscellaneous	
<b>Features</b>	Security lock slot (cable lock sold separately), iTouch Surface Acoustic Wave Technology
<b>MTBF</b>	50,000 hour(s)
<b>Compliant Standards</b>	FCC Class A certified, UL, VCCI, C-Tick, cUL, SEMKO, VESA DPMS, DDC
Power	
<b>Power Supply</b>	Internal
<b>Voltage Required</b>	AC 120/230 V (50/60 Hz)
<b>Power Consumption Operational</b>	22 Watt
<b>Power Consumption Stand by</b>	1 Watt
<b>Power Consumption Sleep</b>	2 Watt
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - 3 years
Environmental Parameters	
<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	20 - 80% (non-condensing)