

Produktinformation



Information

<i>Tillverkare</i>	Elo Touch Solutions
<i>Artnr</i>	E877820

Elo Desktop Touchmonitors 1717L AccuTouch - LED monitor - 17"

The 1717L touch monitor is built to withstand the rigors of continuous public use with a rugged "built for touch" design. Its stylish, thin and modern look is coupled with a retail-focused feature set and is an attractive solution for commercial touch monitor needs. It is well suited for high use public venues where point-of-sale, point-of-information, point-of-service, shelf-level and countertop interactive digital signage and loyalty systems are found. The 1717L with AccuTouch five-wire resistive technology is widely used in retail and hospitality environments based on its proven ability to survive splashing liquids, food and grease. The 1717L touch monitor is environmentally friendly, lightweight and uses less power with state-of-the-art LED backlights in the display panel.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	17"
Aspect Ratio	5:4
Native Resolution	1280 x 1024 at 75 Hz
Brightness	250 cd/m ²
Brightness w/touchscreen	200 cd/m ²
Contrast Ratio	800:1
Colour Support	16.7 million colours
Response Time	5 ms (tr - tf)
Vertical Refresh Rate	56 - 75 Hz
Horizontal Refresh Rate	31.5 - 80 kHz
Horizontal Viewing Angle	+85 / -85
Vertical Viewing Angle	+80 / -80
Screen Coating	Anti-glare
Backlight Technology	LED backlight

Controls & Adjustments	Brightness, contrast, H/V position, sharpness, colour balance, colour temperature, phase, clock, aspect control
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Features	AccuTouch Five-Wire Resistive, touch screen
Colour	Black
Dimensions (WxDxH)	39.2 cm x 21.5 cm x 36.1 cm - with stand
Weight	5.4 kg

Input

Type	Touch-screen - touchscreen
Movement Detection Technology	Resistive

Connectivity

Interfaces	Serial USB VGA
-------------------	----------------

Mechanical

VESA Mounting Interface	75 x 75 mm
--------------------------------	------------

Miscellaneous

Features	Security lock slot (cable lock sold separately), AccuTouch Five-Wire Resistive Touch technology
MTBF	50,000 hour(s)
Compliant Standards	UL, VCCI, C-Tick, BSMI, cUL, CB, CCC, IC, FCC, RoHS, KCC, WEEE, S Mark, China RoHS
Localisation	Worldwide

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	16 Watt
Power Consumption Stand by	1.1 Watt
Power Consumption Sleep	0.5 Watt

Manufacturer Warranty

Service & Support	Limited warranty - 3 years
------------------------------	----------------------------

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)