

Produktinformation



Information

<i>Tillverkare</i>	Extreme Networks
<i>Artnr</i>	AH-SR-2208P-EU

Aerohive Networks SR2208P - Switch - Managed - 8 x 10/100/1000 (PoE+) + 2 x combo SFP - desktop, rack-mountable - PoE+ (124 W)

SR2208P is an 8 + 2 Gigabit Ethernet port, cloud managed, fan less, desktop Layer 3 Lite (L2 and L3 static routing) switch. SR2208P is the optimal fit for situations when you need extra wired port capacity. SR2208P allows you to quickly extend your wiring closet and it is simply auto-provisioned, managed and monitored from Aerohive's public or private cloud based HiveManager network management system. The switch provides the flexibility of either using 8 ports in 802.3af mode or 4 ports in 802.3at mode or any combination of the modes.

Specifikation

General

Device Type	Switch - 8 ports - Managed
Enclosure Type	Desktop, rack-mountable
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000 (PoE+) + 2 x combo SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	124 W
Performance	Switching throughput: 20 Gbps
Capacity	Virtual interfaces (VLANs): 4095
MAC Address Table Size	16000 entries
Jumbo Frame Support	9216 bytes
Routing Protocol	Static IP routing
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, SSH-2, CLI, SCP
Encryption Algorithm	AES, TLS 1.0, SSL 3.0
Authentication Method	TACACS+
Features	Flow control, IGMP snooping, port mirroring, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Jumbo

Compliant Standards	Frames support, LLDP support, Generic Attribute Registration Protocol (GARP), Storm Control, rate limit
	IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ac, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3at
Expansion / Connectivity	
Interfaces	8 x 1000Base-T RJ-45 PoE+ - 30 W 2 x Gigabit LAN RJ-45/SFP uplink 1 x console RJ-45 management
Power	
Voltage Required	AC 120/230 V
Miscellaneous	
MTBF	1,209,148 hours
Localisation	Europe
Dimensions & Weight	
Width	27.9 cm
Depth	17 cm
Height	4.4 cm
Manufacturer Warranty	
Service & Support	Limited warranty - lifetime
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 95% (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C