

Produktinformation



HP EliteDisplay E243i - LED monitor - 24"

Information



<i>Tillverkare</i>	HP
<i>Artnr</i>	1FH49AT#ABB-R

Style meets substance in a strikingly modern business display crafted for optimal viewing, productivity, and ergonomics. The HP EliteDisplay E243i 24-inch Monitor has a 3-sided micro-edge bezel for seamless multi-display tiling and 4-way adjustability so you can comfortably power through the day.

Specifikation

General

Status	W2
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A
Energy Consumption per Year	38 kWh
Power Consumption (On mode)	26 W
Diagonal Size	24"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:10
Native Resolution	WUXGA 1920 x 1200 at 60 Hz
Pixel Pitch	0.27 mm
Brightness	300 cd/m ²
Contrast Ratio	1000:1 / 10000000:1 (dynamic)
Response Time	5 ms (On/Off)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, anti-static
Backlight Technology	LED backlight
Features	BrightView, HDCP, arsenic-free glass
Colour	Black

Dimensions (WxDxH) 53.2 cm x 21.39 cm x 36.23 cm - with stand

Weight 6.36 kg

Connectivity

Interfaces HDMI (HDCP) DisplayPort (HDCP) VGA USB 3.0 upstream (Type B) 2 x USB 3.0 downstream (Type A)

Mechanical

Display Position Adjustments Height, pivot (rotation), swivel, tilt

Tilt Angle -5/+23

Swivel Angle 45

Rotation Angle 90

Height Adjustment 150 mm

VESA Mounting Interface 100 x 100 mm

Miscellaneous

Features Security lock slot (cable lock sold separately)

Compliant Standards Plug and Play, TUV GS, VCCI, BSMI, WHQL, CB, CCC, FCC, ISO 9241-307, WEEE, ICES, S Mark, cTUVus, ERP, CEL, ISC, RCM, MSIP, CoC, low halogen

Security Slot Type Kensington security slot

Power

Voltage Required AC 120/230 V

Power Consumption Operational 35 Watt

Power Consumption Stand by 0.5 Watt

Dimensions & Weight

Dimensions & Weight Details With stand - width: 53.2 cm - depth: 21.39 cm - height: 36.23 cm - weight: 6.36 kg Without stand - width: 53.2 cm - depth: 4.64 cm - height: 35.13 cm

Environmental Standards

TCO Certified TCO Certified Displays 7, TCO Certified Edge Displays

ENERGY STAR Certified Yes

Environmental Parameters

Min Operating Temperature 5 °C

Max Operating Temperature 35 °C

Humidity Range Operating 20 - 80%