

Produktinformation



HP EliteDisplay E273 - LED monitor - Full HD (1080p) - 27"

Information



Tillverkare	HP
Artnr	1FH50AA#ABB-R

Style meets substance in a strikingly modern business display, crafted for optimal viewing, productivity, and ergonomics. The HP EliteDisplay E273 27-inch monitor has a 3-sided micro-edge bezel for seamless multi-display tiling and 4-way adjustability, so you can comfortably power through your day.

Specifikation

General

Status	W2
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A+
Energy Consumption per Year	24 kWh
Power Consumption (On mode)	16 W
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.3114 mm
Pixel Per Inch	81.59
Brightness	250 cd/m ²
Contrast Ratio	1000:1 / 5000000:1 (dynamic)
Colour Support	16.7 million colours
Response Time	5 ms (On/Off)
Vertical Refresh Rate	50 - 60 Hz
Horizontal Refresh Rate	30 - 80 kHz

Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	WLED
Colour Temperature	6500K
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features	HDCP, 72% NTSC colour gamut, Frame Rate Control (FRC), Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, Micro Edge, 94% sRGB colour gamut
Colour	Black (rear cover), silver (front bezel, frame and stand)
Dimensions (WxDxH)	61.09 cm x 21.39 cm x 52.26 cm - with stand
Weight	7.1 kg

Connectivity

Interfaces	HDMI (HDCP) DisplayPort (HDCP) VGA USB 3.0 upstream (Type B) 2 x USB 3.0 downstream (Type A)
-------------------	--

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+22
Swivel Angle	90
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately), integrated cable management, detachable stand, direct mountable, VESA interface support
Cables Included	1 x VGA cable - 1.8 m 1 x DisplayPort cable - 1.8 m 1 x USB 3.0 to USB 3.0 type B cable - 1.8 m
Backlight Life	30,000 hours
Compliant Standards	Plug and Play, CSA, UL, VCCI, BSMI, NOM, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, MEPS, KC, CECP, CEL, EAC, ISC, low halogen, ICE, SmartWay
Security Slot Type	Kensington security slot

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	45 Watt
Power Consumption Stand by	0.3 Watt
On / Off Switch	Yes

Software / System Requirements

Included Software HP Display Assistant

Dimensions & Weight

Dimensions & Weight Details With stand - width: 61.09 cm - depth: 21.39 cm - height: 52.26 cm
- weight: 7.1 kg Without stand - width: 61.09 cm - depth: 5.02 cm -
height: 36.4 cm - weight: 4.48 kg

Environmental Standards

TCO Certified TCO Certified Displays 7, TCO Certified Edge Displays

ENERGY STAR Certified Yes

Manufacturer Warranty

Service & Support Limited warranty - 3 years

Environmental Parameters

Min Operating Temperature 5 °C

Max Operating Temperature 35 °C

Humidity Range Operating 20 - 80% (non-condensing)