

Produktinformation



HP EliteDisplay E273q - LED monitor - 27"

Information



Tillverkare	HP
Artnr	1FH52AA#ABB-R

Style meets substance in the strikingly modern HP EliteDisplay E273q 27-inch QHD monitor, a Quad HD display, crafted for optimal viewing, productivity, and ergonomics with a 3-sided micro-edge bezel for seamless multi-display tiling, flexible USB-C connectivity, and 4-way adjustable comfort.

Specifikation

General

Status	W2
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class B
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.2331 mm
Pixel Per Inch	108.8
Brightness	350 cd/m ²
Contrast Ratio	1000:1 / 5000000:1 (dynamic)
Colour Support	16.7 million colours
Response Time	5 ms (On/Off)
Vertical Refresh Rate	50 - 60 Hz
Horizontal Refresh Rate	30 - 90 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178

Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	WLED
Colour Temperature	6500K
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features	HDCP, Frame Rate Control (FRC), Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic-free glass, Micro Edge, 99.6% sRGB colour gamut
Colour	Black (rear cover), silver (front bezel, frame and stand)
Dimensions (WxDxH)	61.26 cm x 21.4 cm x 52.29 cm - with stand
Weight	7.4 kg

Connectivity

Interfaces	HDMI (HDCP) DisplayPort (HDCP) VGA USB-C upstream (HDCP) 2 x USB 3.0 downstream (Type A)
-------------------	--

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+22
Swivel Angle	90
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately), integrated cable management, detachable stand, direct mountable, VESA interface support
Cables Included	1 x HDMI cable - 1.8 m 1 x DisplayPort cable - 1.8 m 1 x USB 3.1 Type A to Type C cable - 1.8 m
Backlight Life	30,000 hours
Compliant Standards	Plug and Play, TUV GS, VCCI, BSMI, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, WEEE, PSE Mark, cTUVus, MEPS, CECF, CEL, EAC, ISC, RCM, MSIP, CoC, low halogen, ICE, SmartWay
Security Slot Type	Kensington security slot

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	75 Watt
Power Consumption Stand by	0.5 Watt
On / Off Switch	Yes

Software / System Requirements

Included Software	HP Display Assistant
--------------------------	----------------------

Dimensions & Weight

Dimensions & Weight Details	With stand - width: 61.26 cm - depth: 21.4 cm - height: 52.29 cm - weight: 7.4 kg Without stand - width: 61.26 cm - depth: 4.93 cm - height: 36.4 cm - weight: 4.6 kg
--	---

Environmental Standards

TCO Certified	TCO Certified Displays 8, TCO Certified Edge Displays
ENERGY STAR Certified	Yes

Manufacturer Warranty

Service & Support	Limited warranty - 3 years
------------------------------	----------------------------

Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)