

Produktinformation



HP Z23n G2 - LED monitor - Full HD (1080p) - 23"

Information



Tillverkare HP
Artnr 1JS06A4#ABB-R_G

Be a productive powerhouse with the sleek HP Z23n G2 23-inch Display. This virtually seamless Full HD display is factory-tested for reliability and longevity with integrated color calibration, uninterrupted multi-screen tiling, and expansive device connections.

Specifikation

General

Status	W1
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A
Energy Consumption per Year	31 kWh
Power Consumption (On mode)	21 W
Diagonal Size	23"
Viewable Size	23"
Built-in Devices	USB 3.0 hub
Panel Type	AH-IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Per Inch	96
Brightness	250 cd/m ²
Contrast Ratio	1000:1 / 10000000:1 (dynamic)
Colour Support	16.7 million colours
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	50 - 75 Hz
Horizontal Refresh Rate	30 - 84 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178

Screen Coating	Anti-glare
Backlight Technology	WLED
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features	HDCP, On-screen Digital Controls, Mercury free, Factory Calibration, arsenic-free glass, Micro Edge, 94% sRGB colour gamut
Colour	Space Silver, black pearl chin
Dimensions (WxDxH)	50.93 cm x 20.5 cm x 45.72 cm - with stand
Weight	5.9 kg
Connectivity	
Interfaces	VGA HDMI (HDCP) DisplayPort (HDCP) USB 3.0 upstream 2 x USB 3.0 downstream
Mechanical	
Display Position Adjustments	Pivot (rotation), swivel, tilt
Tilt Angle	-5/+22
Swivel Angle	90
Rotation Angle	90
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), detachable stand, VESA 100 x 100 mm
Cables Included	1 x USB cable - 1.8 m 1 x DisplayPort cable - 2 m
Backlight Life	30,000 hours
Compliant Standards	VCCI, BSMI, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, WEEE, ICES, cTUVus, MEPS, E-Standby, KC, ERP, CEL, ISC, RCM, MSIP, SEPA, CoC, CU, CE/EMC
Localisation	English / Europe
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	18 Watt
Power Consumption Stand by	0.5 Watt
On / Off Switch	Yes
Software / System Requirements	
Included Software	HP Display Assistant
Dimensions & Weight	

Dimensions & Weight Details	Without stand - width: 52.1 cm - depth: 31.17 cm - height: 4.33 cm - weight: 3.3 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8, TCO Certified Edge Displays
ENERGY STAR Certified	Yes
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)