

## Produktinformation



### HP t530 - tower - GX-215JJ 1.5 GHz - 4 GB - flash 8 GB

#### Information



Tillverkare	HP
Artnr	2DH77AA-R_G

With a modern, new look and a small size, the HP t530 has raised the stakes for thin client design. Multiple deployment options allow this thin client to fit into any workspace.

## Specifikation

### General

Status	W1
Type	Thin client
Product Form Factor	Tower
Embedded Security	Trusted Platform Module (TPM 2.0) Security Chip

### Processor / Chipset

CPU	AMD GX-215JJ 1.5 GHz
Max Turbo Speed	2 GHz
Number of Cores	Dual-Core
CPU Qty	1
Max CPU Qty	1
CPU Upgradability	Not upgradable
Processor Main Features	AMD Turbo CORE Technology

### Cache Memory

Installed Size	L2 Cache - 1 MB
Cache Per Processor	1 MB

### RAM

Installed Size	4 GB / 16 GB (max)
Technology	DDR4 SDRAM - non-ECC
Effective Memory Speed	1866 MHz

<b>Form Factor</b>	SO-DIMM 260-pin
<b>Slots</b>	1 (Total) / 0 (empty)
<b>Features</b>	Unbuffered
<b>Configuration Features</b>	1 x 4 GB

#### Hard Drive

<b>Type</b>	Flash - M.2
<b>Capacity</b>	1 x 8 GB

#### Optical Storage

<b>Type</b>	No optical drive
-------------	------------------

#### Monitor

<b>Monitor Type</b>	None.
---------------------	-------

#### Graphics Controller

<b>Graphics Processor</b>	AMD Radeon R2E
<b>Video Interfaces</b>	DisplayPort
<b>Max Monitors Supported</b>	2

#### Input Device

<b>Type</b>	Mouse, keyboard
-------------	-----------------

#### Keyboard

<b>Keyboard Name</b>	HP Business Slim Keyboard
<b>Interface</b>	USB

#### Mouse

<b>Technology</b>	Optical
<b>Interface</b>	USB

#### Networking

<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Features</b>	Wake on LAN (WoL), DHCP support, PXE support
<b>Compliant Standards</b>	IEEE 802.1x

#### Expansion / Connectivity

<b>Slots</b>	1 (total) / 0 (free) x M.2 Card
<b>Interfaces</b>	1 x USB 3.1 Gen 1 (1 in front) 1 x USB-C Gen 1 (1 in front) 2 x USB 2.0 (2 rear) Headphones/microphone (1 in front) 2 x DisplayPort 1 x LAN (Gigabit Ethernet) - RJ-45

#### Miscellaneous

<b>Theft/Intrusion Protection</b>	Security lock slot (cable lock sold separately)
<b>Security Slot Type</b>	Kensington security slot
<b>Compliant Standards</b>	UL, VCCI, GS, CB, CCC, FCC, RoHS, KCC, WEEE, ICES, MEPS, ERP, CECP, EMI/EMS Class B, low halogen

Power

Device Type	Power adapter
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	45 Watt

Environmental Standards

ENERGY STAR Certified	Yes
-----------------------	-----

Dimensions & Weight

Width	3.5 cm
Depth	20 cm
Height	20 cm
Weight	962.8 g

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)