

Produktinformation



HP t530 - tower - GX-215JJ 1.5 GHz - 8 GB - flash 16 GB

Information



Tillverkare	HP
Artnr	2RC23EA-D1

With a modern, new look and a small size, the HP t530 has raised the stakes for thin client design. Multiple deployment options allow this thin client to fit into any workspace.

Specifikation

General

Status	D1
Type	Thin client
Product Form Factor	Tower
Embedded Security	Trusted Platform Module (TPM 2.0) Security Chip

Processor / Chipset

CPU	AMD GX-215JJ 1.5 GHz
Max Turbo Speed	2 GHz
Number of Cores	Dual-Core
CPU Qty	1
Max CPU Qty	1
CPU Upgradability	Not upgradable
Processor Main Features	AMD Turbo CORE Technology

Cache Memory

Installed Size	L2 Cache - 1 MB
Cache Per Processor	1 MB

RAM

Installed Size	8 GB / 16 GB (max)
Technology	DDR4 SDRAM - non-ECC
Effective Memory Speed	1866 MHz
Rated Memory Speed	1866 MHz

Memory Specification Compliance	PC4-14900
Form Factor	SO-DIMM 260-pin
Slots	1 (Total) / 0 (empty)
Features	Unbuffered
Configuration Features	1 x 8 GB
Hard Drive	
Type	Flash - M.2
Capacity	1 x 16 GB
Features	Multi-level cell (MLC)
Optical Storage	
Type	No optical drive
Monitor	
Monitor Type	None.
Graphics Controller	
Multi-GPU Configuration	1 single GPU card / integrated GPU
Graphics Processor	AMD FirePro W2100 / AMD Radeon R2E
Video Interfaces	DisplayPort
Max Monitors Supported	2
Input Device	
Type	Mouse, keyboard
Keyboard	
Keyboard Name	HP Business Slim Smart Card CCID Keyboard
Interface	USB
Mouse	
Technology	Optical
Interface	USB
Networking	
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Wake on LAN (WoL), DHCP support, PXE support
Compliant Standards	IEEE 802.1x
Expansion / Connectivity	
Slots	1 (total) / 0 (free) x M.2 Card
Interfaces	1 x USB 3.1 Gen 1 - Type C (1 in front) 3 x USB 3.1 Gen 1 (1 front, 2 rear) 2 x USB 2.0 2 x DisplayPort 1 x LAN (Gigabit Ethernet) Headphones/microphone (1 in front)
Miscellaneous	
Theft/Intrusion Protection	Security lock slot (cable lock sold separately)

Security Slot Type	Kensington security slot
Compliant Standards	UL, VCCI, GS, CB, CCC, FCC, RoHS, KCC, WEEE, CISPR, ICES, MEPS, ERP, CECP, EMI

Power

Device Type	Power adapter
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	45 Watt

Operating System / Software

OS Provided	HP ThinPro
--------------------	------------

Dimensions & Weight

Width	3.5 cm
Depth	20 cm
Height	20 cm
Weight	962.8 g

Dimensions & Weight (Shipping)

Shipping Weight	1.9197 kg
------------------------	-----------

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)