

Produktinformation



HP t530 - tower - GX-215JJ 1.5 GHz - 4 GB - flash 16 GB

Information



Tillverkare	HP
Artnr	2RC29ET-D1

With a modern, new look and a small size, the HP t530 has raised the stakes for thin client design. Multiple deployment options allow this thin client to fit into any workspace.

Specifikation

General

Status	D1
Type	Thin client
Product Form Factor	Tower
Embedded Security	Trusted Platform Module (TPM 2.0) Security Chip

Processor / Chipset

CPU	AMD GX-215JJ 1.5 GHz
Max Turbo Speed	2 GHz
Number of Cores	Dual-Core
CPU Qty	1
Max CPU Qty	1
CPU Upgradability	Not upgradable
Processor Main Features	AMD Turbo CORE Technology

Cache Memory

Installed Size	L2 Cache - 1 MB
Cache Per Processor	1 MB

RAM

Installed Size	4 GB / 16 GB (max)
Technology	DDR4 SDRAM - non-ECC
Effective Memory Speed	1866 MHz

Form Factor	SO-DIMM 260-pin
Slots	1 (Total) / 0 (empty)
Features	Unbuffered
Configuration Features	1 x 4 GB

Hard Drive

Type	Flash - M.2
Capacity	1 x 16 GB

Optical Storage

Type	No optical drive
-------------	------------------

Monitor

Monitor Type	None.
---------------------	-------

Graphics Controller

Graphics Processor	AMD Radeon R2E
Video Interfaces	DisplayPort
Max Monitors Supported	2

Input Device

Type	Mouse
-------------	-------

Mouse

Technology	Optical
Interface	USB

Networking

Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Wake on LAN (WoL), DHCP support, PXE support
Compliant Standards	IEEE 802.1x

Expansion / Connectivity

Slots	1 (total) / 0 (free) x M.2 Card
Interfaces	1 x USB-C 3.1 Gen 1 (1 in front) 3 x USB 3.1 Gen 1 (1 front, 2 rear) 2 x USB 2.0 2 x DisplayPort 1 x LAN (Gigabit Ethernet) Headphones/ microphone (1 in front)

Miscellaneous

Theft/Intrusion Protection	Security lock slot (cable lock sold separately)
Security Slot Type	Kensington security slot
Compliant Standards	UL, VCCI, GS, CB, CCC, FCC, RoHS, KCC, WEEE, CISPR, ICES, MEPS, ERP, CECP, EMI
Pricing Type	Promo

Power

Device Type	Power adapter
--------------------	---------------

Nominal Voltage AC 120/230 V (50/60 Hz)

Power Provided 45 Watt

Operating System / Software

OS Provided Microsoft Windows Embedded Standard 7E

Dimensions & Weight

Width 3.5 cm

Depth 20 cm

Height 20 cm

Weight 962.8 g

Environmental Parameters

Min Operating Temperature 10 °C

Max Operating Temperature 40 °C

Humidity Range Operating 10 - 90% (non-condensing)