

Produktinformation



HP t630 - tower - GX-420GI 2 GHz - 4 GB - flash 32 GB

Information



Tillverkare HP
Artnr 2RC38EA

Optimize your cloud-based deployments with the powerful, highly configurable, and long-lifecycle HP t630. Support your business now and in the future with powerful processing, dual Ultra HD / 4K display compatibility, and possibilities for device and network connectivity and local storage.

Specifikation

General

Status	N1
Type	Thin client
Product Form Factor	Tower
Embedded Security	Trusted Platform Module (TPM 2.0) Security Chip

Processor / Chipset

CPU	AMD GX-420GI 2 GHz
Max Turbo Speed	2.2 GHz
Number of Cores	Quad-Core
CPU Qty	1
Max CPU Qty	1
CPU Upgradability	Not upgradable
Processor Main Features	AMD Turbo CORE Technology

Cache Memory

Installed Size	L2 Cache - 2 MB
Cache Per Processor	2 MB

RAM

Installed Size	4 GB / 32 GB (max)
Technology	DDR4 SDRAM - non-ECC
Effective Memory Speed	1866 MHz
Rated Memory Speed	1866 MHz

Memory Specification Compliance	PC4-14900
Form Factor	SO-DIMM 260-pin
Slots	2 (Total) / 1 (empty)
Features	Unbuffered
Configuration Features	1 x 4 GB

Hard Drive

Type	Flash - M.2
Capacity	1 x 32 GB

Optical Storage

Type	No optical drive
-------------	------------------

Monitor

Monitor Type	None.
---------------------	-------

Graphics Controller

Graphics Processor	AMD Radeon R7E
Video Interfaces	VGA, DisplayPort
Max Monitors Supported	2

Networking

Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Wake on LAN (WoL), PXE support

Expansion / Connectivity

Slots	1 (total) / 0 (free) x M.2 Card - 2280 1 (total) / 1 (free) x M.2 Card - 2242
Interfaces	4 x USB 2.0 (2 front, 2 rear) 3 x USB 3.0 (2 front, 1 internal) 2 x DisplayPort 1 x PS/2 keyboard 1 x PS/2 mouse 1 x LAN (Gigabit Ethernet) 1 x serial 1 x headphones/microphone (1 in front) 1 x audio line-out/line-in 1 x VGA

Miscellaneous

Theft/Intrusion Protection	Security lock slot (cable lock sold separately)
Security Slot Type	Kensington security slot
Compliant Standards	FCC Class B certified, UL, GS, CB, CCC, RoHS, ICES Class B, MEPS, KCC Class B, ERP, CECP, VCCI Class B, CISPR Class B
TAA Compliant	Yes

Power

Device Type	Power adapter
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	65 Watt

Environmental Standards

ENERGY STAR Certified	Yes
------------------------------	-----

Dimensions & Weight

Width	12 cm
Depth	22 cm
Height	25.1 cm
Weight	1.52 kg

Dimensions & Weight (Shipping)

Shipping Weight	4.1 kg
-----------------	--------

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)