

Produktinformation



HP t630 - tower - GX-420GI 2 GHz - 8 GB - flash 32 GB

Information



Tillverkare HP
Artnr 2ZV00AA

Optimize your cloud-based deployments with the powerful, highly configurable, and long-lifecycle HP t630. Support your business now and in the future with powerful processing, dual Ultra HD / 4K display compatibility, and possibilities for device and network connectivity and local storage.

Specifikation

General

Status	N1
Type	Thin client
Product Form Factor	Tower
Embedded Security	Trusted Platform Module (TPM 2.0) Security Chip

Processor / Chipset

CPU	AMD GX-420GI 2 GHz
Max Turbo Speed	2.2 GHz
Number of Cores	Quad-Core
CPU Qty	1
Max CPU Qty	1
CPU Upgradability	Not upgradable
Processor Main Features	AMD Turbo CORE Technology

Cache Memory

Installed Size	L2 Cache - 2 MB
Cache Per Processor	2 MB

RAM

Installed Size	8 GB / 32 GB (max)
Technology	DDR4 SDRAM - non-ECC
Effective Memory Speed	1866 MHz
Rated Memory Speed	1866 MHz

Memory Specification Compliance	PC4-14900
Form Factor	SO-DIMM 260-pin
Slots	2 (Total) / 0 (empty)
Features	Unbuffered
Configuration Features	2 x 4 GB
Hard Drive	
Type	Flash - M.2
Capacity	1 x 32 GB
Optical Storage	
Type	No optical drive
Monitor	
Monitor Type	None.
Graphics Controller	
Graphics Processor	AMD Radeon R7E
Video Interfaces	DisplayPort
Max Monitors Supported	2
Input Device	
Type	Keyboard
Keyboard	
Keyboard Name	HP Business Slim Keyboard
Interface	USB
Networking	
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
Slots	1 (total) / 0 (free) x M.2 Card - 2280 1 (total) / 1 (free) x M.2 Card - 2242
Interfaces	2 x DisplayPort 1 x LAN (Gigabit Ethernet) - RJ-45 1 x headphones/microphone (1 in front) 4 x USB 2.0 (2 front, 2 rear) 3 x USB 3.0 (2 front, 1 internal) 1 x PS/2 keyboard 1 x PS/2 mouse 1 x serial 1 x audio line-out/line-in
Miscellaneous	
Theft/Intrusion Protection	Security lock slot (cable lock sold separately)
Security Slot Type	Kensington security slot
Compliant Standards	FCC Class B certified, UL, GS, CB, CCC, RoHS, ICES Class B, MEPS, KCC Class B, ERP, CECP, VCCI Class B, CISPR Class B
Power	
Device Type	Power adapter

Nominal Voltage AC 120/230 V (50/60 Hz)

Power Provided 65 Watt

Environmental Standards

ENERGY STAR Certified Yes

Dimensions & Weight

Width 12 cm

Depth 22 cm

Height 25.1 cm

Weight 1.52 kg

Dimensions & Weight (Shipping)

Shipping Weight 4.1 kg

Environmental Parameters

Min Operating Temperature 10 °C

Max Operating Temperature 40 °C

Humidity Range Operating 10 - 90% (non-condensing)