

Produktinformation



Information



Tillverkare

HP

Artnr

3AQ05AV-D1

HP Workstation Z2 Mini G4 Performance - mini - no CPU - 0 GB - no HDD

Specifikation

General

Status	D1
Type	Workstation
Product Form Factor	Mini
Built-in Devices	Speaker
Embedded Security	Trusted Platform Module (TPM 2.0) Security Chip
Colour	Space grey with black chrome accents

Processor / Chipset

CPU	No CPU
Max CPU Qty	1
CPU Upgradability	Upgradable
CPU Socket	LGA1151 Socket
Chipset Type	Intel C246

RAM

Installed Size	0 GB / 32 GB (max)
Technology	DDR4 SDRAM
Form Factor	SO-DIMM 260-pin
Slots	2 (Total) / 2 (empty)

Hard Drive

Type	No HDD
------	--------

Storage Controller

Type	1 x SATA
------	----------

Controller Interface Type	SATA 6Gb/s
Optical Storage	
Type	No optical drive
Monitor	
Monitor Type	None.
Graphics Controller	
Graphics Processor	No graphics
Audio Output	
Sound Output Mode	Stereo
Compliant Standards	High Definition Audio
Networking	
Ethernet Controller	Intel I219-LM
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol	ASF 2.0
Features	Wake on LAN (WoL), PXE support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3z, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1as, IEEE 802.3az
Expansion / Connectivity	
Bays	1 (total) / 1 (free) x internal 2.5"
Slots	1 (total) / 1 (free) x PCIe 3.0 x16 1 (total) / 1 (free) x M.2 Card - 2230 (x1 mode) 1 (total) / 1 (free) x M.2 Card - 2280 (x4 mode)
Interfaces	4 x USB 3.0 (2 front, 2 rear) (one of them is charging) 1 x headphones/microphone (1 in front) 1 x LAN (Gigabit Ethernet) 3 x DisplayPort 2 x USB-C 3.1 Gen 2 (one of them is charging)
Miscellaneous	
Theft/Intrusion Protection	Security lock slot (cable lock sold separately)
Security Slot Type	Kensington security slot
VESA Mounting Interface	Yes
Compliant Standards	ACPI, RoHS, WEEE
Pricing Type	CTO
Power	
Device Type	Power adapter
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Factor Correction	Yes (active)
Dimensions & Weight	
Width	21.6 cm
Depth	21.6 cm

Height	5.8 cm
Weight	2.04 kg

Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 85% (non-condensing)