

Produktinformation



HP HC271 Clinical Review Monitor - Healthcare - LED monitor - 27"

Information



Tillverkare	HP
Artnr	3ME70AA#ABB-D1

Deploy a display optimized for patient rooms, nurses stations, medical carts, and public areas with the HP Healthcare Edition HC271. It's built for easy, repeatable sanitization after every patient engagement and is DICOM Part 14 compliant for accurate viewing of medical images.

Specifikation

General

Status	D1
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class B
Energy Consumption per Year	45 kWh
Power Consumption (On mode)	31 W
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	AHVA
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.2331 mm
Pixel Per Inch	108.79
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Response Time	12 ms (grey-to-grey)
Vertical Refresh Rate	50 - 60 Hz
Horizontal Refresh Rate	30 - 90 kHz
Horizontal Viewing Angle	178

Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Features	Mercury free, arsenic free, Zero Bright Dot Warranty
Colour	White
Dimensions (WxDxH)	64.4 cm x 19.7 cm x 39.3 cm - with stand
Weight	7.16 kg
Connectivity	
Interfaces	DisplayPort (HDCP) HDMI (HDCP) VGA 2 x USB 3.0 downstream USB 3.0 upstream
Mechanical	
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
Compliant Standards	Plug and Play, UL, VCCI, BSMI, NOM, TUV S, WHQL, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, MEPS, CECP, EAC, ISC, low halogen, CE/EMC
Localisation	English / Europe
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	45 Watt
Power Consumption Stand by	0.5 Watt
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 64.4 cm - depth: 19.7 cm - height: 39.3 cm - weight: 7.31 kg Without stand - width: 64.4 cm - depth: 5.1 cm - height: 39.3 cm - weight: 5 kg
Dimensions & Weight (Shipping)	
Shipping Width	75.1 cm
Shipping Depth	19 cm
Shipping Height	50.6 cm
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)