

Produktinformation



HP EliteDisplay E273d Docking Monitor - LED monitor - Full HD (1080p) - 27"

Information



Tillverkare

HP

Artnr

5WN63AT#ABB-D1

Specifikation

General

Status	D1
Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	720p webcam, dual array microphone, USB 3.1 Gen1/USB-C hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.311 mm
Brightness	250 cd/m ²
Contrast Ratio	1000:1 / 5000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	60 Hz
Horizontal Refresh Rate	80 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Backlight Technology	LED backlight
Bezel Type	Flat front
Features	HDCP, On-screen Digital Controls, arsenic-free glass, DisplayLink Technology
Dimensions (WxDxH)	61.09 cm x 4.63 cm x 36.3 cm - without stand

Connectivity	
Interfaces	HDMI (HDCP) USB-C upstream/DisplayPort with Power Delivery VGA USB 4 x USB 3.1 downstream with Battery Charging Audio line-in/out Audio line-in Network (RJ-45) DisplayPort output
Miscellaneous	
Features	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
Cables Included	1 x USB cable 1 x USB-C cable
Compliant Standards	Plug and Play, TUV GS, VCCI, BSMI, NOM, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, MEPS, CEL, EAC, ISC, low halogen, Mercury- free
Localisation	English / Europe
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	40 Watt
Power Consumption Stand by	0.5 Watt
Software / System Requirements	
Included Software	HP Display Assistant, CyberLink Youcam
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 61.09 cm - depth: 21.4 cm - height: 50.85 cm - weight: 7.52 kg
Dimensions & Weight (Shipping)	
Shipping Width	73.2 cm
Shipping Depth	28.2 cm
Shipping Height	44.6 cm
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)