

Produktinformation



HP P24h G4 - LED monitor - Full HD (1080p) - 24"

Information



Tillverkare	HP
Artnr	7VH44AA#ABB

See more of your work onscreen with less window toggling on the HP P24h G4 monitor. It has business-class presentation features, adjustable comfort, stereo audio, and advanced connectivity to complement today's workspaces.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A+
Energy Consumption per Year	20.8 kWh
Power Consumption (On mode)	14.28 W
Diagonal Size	24"
Viewable Size	23.8"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.274 mm
Pixel Per Inch	93
Brightness	250 cd/m ²
Contrast Ratio	1000:1 / 8000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	48 - 75 Hz
Horizontal Refresh Rate	30 - 86 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare

Backlight Technology	LED backlight
Colour Temperature	9300K, 5000K, 6500K
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Bezel Type	Flat front
Features	HDCP, 72% NTSC colour gamut, Low Blue Light Mode, Flicker Free technology, Color Calibrated, 3-sided micro-edge, 6-bit + A-FRC Color Depth
Colour	Black
Dimensions (WxDxH)	53.82 cm x 21.16 cm x 46.43 cm - with stand
Weight	4.51 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	2 Watt
Connectivity	
Interfaces	DisplayPort (HDCP) HDMI (HDCP) VGA Audio line-in (mini-jack)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+23
Swivel Angle	360
Rotation Angle	180
Height Adjustment	100 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), arsenic free, mercury free
Cables Included	1 x VGA cable - 1.8 m 1 x audio cable - 1.8 m
Backlight Life	30,000 hours
Compliant Standards	Plug and Play, CSA, UL, VCCI, BSMI, NOM, TUV S, WHQL, CB, CCC, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, ICES, MEPS, KC, CEL, EAC, CEL Grade 1, ISC, CP65, low halogen, DisplayPort 1.2, IEEE 1680, ISO 11469, ISO 1043
Localisation	English / Europe
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	22 Watt
Power Consumption Stand by	0.5 Watt

Software / System Requirements

Included Software HP Display Assistant

Dimensions & Weight

Dimensions & Weight Details With stand - width: 53.82 cm - depth: 21.16 cm - height: 46.43 cm - weight: 4.51 kg Without stand - width: 43.82 cm - depth: 4.59 cm - height: 32.56 cm - weight: 2.53 kg

Dimensions & Weight (Shipping)

Shipping Width 59.8 cm

Shipping Depth 16.5 cm

Shipping Height 41.5 cm

Shipping Weight 6.04 kg

Environmental Standards

TCO Certified TCO Certified Displays 8

ENERGY STAR Certified Yes

ENERGY STAR Version 8.0

Manufacturer Warranty

Service & Support Limited warranty - 3 years

Environmental Parameters

Min Operating Temperature 5 °C

Max Operating Temperature 35 °C

Humidity Range Operating 20 - 80% (non-condensing)