

Produktinformation



HP P24q G4 - P-Series - LED monitor - 23.8"

Information



<i>Tillverkare</i>	HP
<i>Artnr</i>	8MB10AA#ABB

Enjoy a stylish, height-adjustable display with sharp QHD resolution and ultra-wide viewing angles on the HP P24q 23.8" monitor. This ultra slim, 3-sided micro-edge display comes at a great value with convenient HDMI and VGA connectivity.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	23.8"
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 (VGA: 60 Hz, HDMI: 60 Hz)
Pixel Pitch	0.2058 mm
Pixel Per Inch	123
Brightness	250 cd/m ²
Contrast Ratio	1000:1 / 10000000:1 (dynamic)
Response Time	5 ms (grey-to-grey)
Vertical Refresh Rate	50 - 60 Hz
Horizontal Refresh Rate	30 - 80 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Colour Temperature	6500K
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Bezel Type	Flat front

Features	High Frame Rate Control (Hi-FRC), 99% sRGB colour gamut, Flicker Free technology, 3-sided micro-edge, 6-bit + FRC Color Depth
Colour	Black
Dimensions (WxDxH)	54.06 cm x 21.16 cm x 46.33 cm - with stand
Weight	5.59 kg
Connectivity	
Interfaces	HDMI VGA
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+23
Swivel Angle	360
Rotation Angle	90
Height Adjustment	100 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), detachable stand, VESA interface support, HDCP Compliant, arsenic free, mercury free
Cables Included	1 x HDMI cable - 1.8 m
Backlight Life	30,000 hours
Compliant Standards	Plug and Play, BSMI, NOM, WHQL, CB, CCC, FCC, ISO 9241-307, ICES, S Mark, cTUVus, TUV Bauart, China Energy Label Level 2, CEC, ERP, CECP, CEL, EAC, UAE, Ukraine Energy Label
Localisation	English / Europe
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	26 Watt
Power Consumption Stand by	0.5 Watt
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 54.06 cm - depth: 21.16 cm - height: 46.33 cm - weight: 5.59 kg Without stand - width: 54.06 cm - depth: 4.69 cm - height: 32.25 cm - weight: 3.42 kg
Dimensions & Weight (Shipping)	
Shipping Width	63.9 cm
Shipping Depth	22.5 cm
Shipping Height	41.9 cm
Shipping Weight	7.59 kg
Manufacturer Warranty	

Service & Support	Limited warranty - parts and labour - 3 years - on-site
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)