

Produktinformation



HP E24t G4 - E-Series - LED monitor - Full HD (1080p) - 24"

Information



Tillverkare

HP

Artnr

9VH85AA#ABB

Skip the mouse and keyboard and interact with your content onscreen, without distracting glare and fingerprint smudges, with integrated in-cell touch technology that's fast, responsive, and maintains the monitor's sleek, slim profile.

Specifikation

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	24"
Viewable Size	23.8"
Built-in Devices	USB 3.2 Gen 1 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.206 mm
Pixel Per Inch	123
Brightness	300 cd/m ²
Contrast Ratio	1000:1 / 5000000:1 (dynamic)
Response Time	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate	50 - 60 Hz
Horizontal Refresh Rate	30 - 80 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Bezel Type	Flat front

Features	Low Blue Light Mode, Flicker Free technology, in-cell touch technology, 3-sided micro-edge, 6-bit + FRC Color Depth
Colour	Black
Dimensions (WxDxH)	53.94 cm x 20.7 cm x 49.49 cm - with stand
Weight	5.8 kg
Input	
Type	Touchscreen
Connectivity	
Interfaces	DisplayPort 1.2 HDMI VGA 4 x USB 3.2 Gen 1 downstream USB 3.2 Gen 1 upstream (Type B)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+23
Swivel Angle	90
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately), arsenic free
Cables Included	1 x DisplayPort cable 1 x HDMI cable 1 x USB cable
Compliant Standards	CSA, UL, TUV GS, VCCI, BSMI, NOM, TUV S, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, CEC, KC, CECP, CEL, EAC, ISC, SEPA, BIS, low halogen, DisplayPort 1.2, ICE, TUV LBL, Mercury-free, Australian-New Zealand MEPS, Vietnam MEPS, TGM
Localisation	Europe
Security Slot Type	Kensington security slot
Power	
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	25 Watt
Power Consumption Stand by	0.5 Watt
Dimensions & Weight	
Dimensions & Weight Details	With stand - width: 53.94 cm - depth: 20.7 cm - height: 49.49 cm - weight: 5.8 kg Without stand - width: 53.94 cm - depth: 4.7 cm - height: 32.33 cm
Dimensions & Weight (Shipping)	
Shipping Width	61 cm
Shipping Depth	22.5 cm
Shipping Height	39.5 cm

Shipping Weight 8.7 kg

Environmental Standards

TCO Certified TCO Certified Displays 8, TCO Certified Edge Displays

ENERGY STAR Certified Yes

Environmental Parameters

Min Operating Temperature 5 °C

Max Operating Temperature 35 °C

Humidity Range Operating 20 - 80% (non-condensing)