

## Produktinformation



### HP L7014 Retail Monitor - Head Only - LED monitor - 14"

#### Information



|                    |             |
|--------------------|-------------|
| <i>Tillverkare</i> | HP          |
| <i>Artnr</i>       | T6N31AA#ABB |

Complete your retail solution with the HP L7014 Monitor, a modern, virtually borderless widescreen display that delivers easily readable transaction data to customers and associates.

## Specifikation

### General

|                                 |  |
|---------------------------------|--|
| <b>Display Type</b>             | LED-backlit LCD monitor / TFT active matrix  |
| <b>Diagonal Size</b>            | 14"  |
| <b>Panel Type</b>               | TN   |
| <b>Aspect Ratio</b>             | 16:9   |
| <b>Native Resolution</b>        | 1366 x 768 at 60 Hz  |
| <b>Pixel Pitch</b>              | 0.2265 mm  |
| <b>Pixel Per Inch</b>           | 112  |
| <b>Brightness</b>               | 200 cd/m <sup>2</sup>  |
| <b>Contrast Ratio</b>           | 500:1  |
| <b>Colour Support</b>           | 14.4 million colours   |
| <b>Response Time</b>            | 16 ms (On/Off)   |
| <b>Vertical Refresh Rate</b>    | 50 - 76 Hz   |
| <b>Horizontal Refresh Rate</b>  | 24 - 80 kHz  |
| <b>Horizontal Viewing Angle</b> | 90   |
| <b>Vertical Viewing Angle</b>   | 60   |
| <b>Screen Coating</b>           | Anti-glare   |
| <b>Backlight Technology</b>     | LED backlight  |
| <b>Colour Temperature</b>       | 6500K  |
| <b>OSD Languages</b>            | Chinese (traditional), Chinese (simplified), Brazilian Portuguese, English, German, French, Italian, Portuguese, Spanish, Japanese |
| <b>Features</b>                 | 45% colour gamut, Mercury free, arsenic-free glass   |

|  |  |
|--|--|
| <b>Colour</b>                          | HP black, asteroid   |
| <b>Dimensions (WxDxH)</b>              | 33.98 cm x 4.15 cm x 21.8 cm - without stand   |
| Connectivity                           |  |
| <b>Interfaces</b>                      | DisplayPort (HDCP)   |
| Mechanical                             |  |
| <b>VESA Mounting Interface</b>         | 100 x 100 mm   |
| Miscellaneous                          |  |
| <b>Features</b>                        | VESA interface support   |
| <b>Cables Included</b>                 | 1 x power cable - 1.83 m   |
| <b>Backlight Life</b>                  | 15,000 hours   |
| <b>Compliant Standards</b>             | Plug and Play, CSA, UL, VCCI, C-Tick, BSMI, cUL, WHQL, CB, CCC, PSB, FCC, C-ETL, ETL, KCC, ICES, cTUVus, MEPS, E-Standby, ERP, CECP, CEL, ISC, EPA 7.0 |
| <b>Localisation</b>                    | English / Europe   |
| Power                                  |  |
| <b>Voltage Required</b>                | AC 100/240 V (50/60 Hz)  |
| <b>Power Consumption Operational</b>   | 9.5 Watt   |
| <b>Power Consumption Stand by</b>      | 0.5 Watt   |
| Software / System Requirements         |  |
| <b>Included Software</b>               | HP Display Assistant   |
| <b>OS Required</b>                     | Microsoft Windows 7 / 8 / 10   |
| Dimensions & Weight                    |  |
| <b>Dimensions &amp; Weight Details</b> | Without stand - width: 33.98 cm - depth: 4.15 cm - height: 21.8 cm With stand - weight: 1.68 kg  |
| Dimensions & Weight (Shipping)         |  |
| <b>Shipping Width</b>                  | 44.2 cm  |
| <b>Shipping Depth</b>                  | 42.6 cm  |
| <b>Shipping Height</b>                 | 31.6 cm  |
| <b>Shipping Weight</b>                 | 2.8 kg   |
| Manufacturer Warranty                  |  |
| <b>Service &amp; Support</b>           | Limited warranty - parts and labour - 3 years  |
| Environmental Parameters               |  |
| <b>Min Operating Temperature</b>       | 5 °C   |
| <b>Max Operating Temperature</b>       | 35 °C  |
| <b>Humidity Range Operating</b>        | 20 - 80% (non-condensing)  |