

## Produktinformation



### Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	504634-421-REF

## HPE ProLiant DL360 G6 Base - rack-mountable - Xeon E5540 2.53 GHz - 6 GB

Combining concentrated 1U compute power, integrated Lights-Out management, and essential fault tolerance, the HP ProLiant DL360 G6 is optimized for space constrained installations. Intel Xeon processor, Serial Attached SCSI (SAS) and PCI Express Gen2 technology provide a high performance system, ideal for the full range of scale out applications. What's more, the DL360 G6 steps up the fault tolerant in an ultra-dense platform with redundant power, redundant fans, mirrored memory, embedded RAID capability, and full-featured remote Lights-Out management.

## Specifikation

### General

<b>Status</b>	R4
<b>Type</b>	Server
<b>Recommended Use</b>	Small business, corporate business
<b>Product Form Factor</b>	Rack-mountable - 1U
<b>Server Scalability</b>	2-way
<b>Front Accessible Bays Qty</b>	1
<b>Hot-Swap Bays Qty</b>	4

### Processor / Chipset

<b>CPU</b>	Intel Xeon E5540 / 2.53 GHz
<b>Max Turbo Speed</b>	2.8 GHz
<b>Number of Cores</b>	Quad-Core
<b>64-bit Computing</b>	Yes
<b>CPU Qty</b>	1
<b>Max CPU Qty</b>	2
<b>CPU Upgradability</b>	Upgradable
<b>Chipset Type</b>	Intel 5520
<b>Front Side Bus</b>	1066 MHz

Cache Memory	
<b>Installed Size</b>	L3 Cache - 8 MB
<b>Cache Per Processor</b>	8 MB
RAM	
<b>Installed Size</b>	6 GB / 144 GB (max)
<b>Technology</b>	DDR3 SDRAM
<b>Form Factor</b>	DIMM 240-pin
<b>Slots</b>	18 (Total) / 15 (empty)
<b>Features</b>	Registered
<b>Configuration Features</b>	3 x 2 GB
Hard Drive	
<b>Type</b>	No HDD
Storage Controller	
<b>Type</b>	1 x RAID - plug-in card - PCIe x4
<b>Controller Interface Type</b>	SATA 1.5Gb/s / SAS
<b>Storage Controller Name</b>	Smart Array P410i
<b>RAID Level</b>	RAID 0, RAID 1, RAID 5, RAID 10, RAID 50
<b>Buffer Size</b>	256 MB
Optical Storage	
<b>Type</b>	No optical drive
Monitor	
<b>Monitor Type</b>	None.
Graphics Controller	
<b>Type</b>	Integrated
<b>Graphics Processor</b>	ATI ES1000
<b>Video Memory</b>	32 MB
<b>Video Interfaces</b>	VGA
Networking	
<b>Type</b>	Integrated
<b>Interface (Bus) Type</b>	PCI Express x4
<b>Ethernet Ports</b>	2 x Gigabit Ethernet
<b>Ethernet Controller</b>	HP NC382i
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Remote Management Controller</b>	Integrated Lights-Out 2 Standard
<b>Features</b>	Wake on LAN (WoL), ACPI support

<b>Compliant Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3ad (LACP)
Expansion / Connectivity	
<b>Bays</b>	4 (total) / 4 (free) x hot-swap 2.5" SFF 1 (total) / 1 (free) x external 5.25" Slim Line
<b>Slots</b>	1 (total) / 0 (free) x PCIe x8 - low-profile 1 (total) / 1 (free) x PCIe x16 - full-length, full-height 18 (total) / 15 (free) x DIMM 240-pin 2 (total) / 1 (free) x CPU 1 (total) / 1 (free) x PCI-X / 133 MHz
<b>Interfaces</b>	1 x PS/2 keyboard 1 x PS/2 mouse 1 x serial 1 x VGA 3 x USB 2 x LAN (Gigabit Ethernet) 1 x HP iLO
Miscellaneous	
<b>Features</b>	Administrator password, power-on password, keyboard password, disk configuration lock, diskette I/O control, serial port I/O control, quick lock
<b>Compliant Standards</b>	ACPI 1.0b
Power	
<b>Device Type</b>	Power supply - hot-plug
<b>Nominal Voltage</b>	AC 120/230 V (50/60 Hz)
<b>Power Provided</b>	460 Watt
Operating System / Software	
<b>OS Certified</b>	Novell NetWare, Microsoft Windows 2000 Server, Red Hat Linux, SuSe Linux, Microsoft Windows Server 2003, SunSoft Solaris 10
Dimensions & Weight	
<b>Width</b>	42.6 cm
<b>Depth</b>	69.2 cm
<b>Height</b>	4.3 cm
<b>Weight</b>	14.5 kg
Environmental Parameters	
<b>Min Operating Temperature</b>	10 °C
<b>Max Operating Temperature</b>	35 °C
<b>Humidity Range Operating</b>	10 - 90%