

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	603718-B21-REF

HPE ProLiant BL460c G7 - blade - no CPU - 0 GB

As the world's most popular blade, the HP ProLiant BL460c G7 Server offers the ideal balance of performance, scalability, and expandability to make it the standard for data center computing. The BL460c gives IT managers a single platform that can handle any business applications.

Specifikation

General

Status	R4
Type	Server
Recommended Use	Small business, corporate business
Product Form Factor	Blade
Server Scalability	2-way
Hot-Swap Bays Qty	2

Processor / Chipset

CPU	No CPU
Max CPU Qty	2
CPU Upgradability	Upgradable
CPU Socket	LGA1366 Socket
Chipset Type	Intel 5520

RAM

Installed Size	0 GB / 384 GB (max)
Technology	DDR3 SDRAM - Advanced ECC
Form Factor	DIMM 240-pin
Slots	12 (Total) / 12 (empty)
RAM Supported	PC3-8500 - 384 GB registered - ECC PC3-10600 - 48 GB unbuffered - ECC PC3-10600 - 192 GB registered - ECC

Hard Drive	
Type	No HDD
Storage Controller	
Type	1 x SAS-2 - integrated - PCIe x4
Controller Interface Type	SATA 3Gb/s / SAS 6Gb/s
Storage Controller Name	Smart Array P410i
RAID Level	RAID 0, RAID 1
Optical Storage	
Type	No optical drive
Monitor	
Monitor Type	None.
Graphics Controller	
Type	Integrated
Graphics Processor	Matrox G200
Networking	
Type	Integrated
Interface (Bus) Type	PCI Express 2.0 x8
Ethernet Ports	2 x 10 Gigabit Ethernet
Ethernet Controller	HP NC553i
Data Link Protocol	Gigabit Ethernet, 10 Gigabit Ethernet
Remote Management Protocol	SNMP, IPMI 2.0, SMASH CLP
Remote Management Controller	Integrated Lights-Out 3
Features	Wake on LAN (WoL)
Compliant Standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.3ap
Expansion / Connectivity	
Bays	2 (total) / 2 (free) x hot-swap 2.5" SFF
Slots	2 (total) / 2 (free) x CPU 12 (total) / 12 (free) x DIMM 240-pin 2 expansion slot 1 (total) / 1 (free) x SD card
Interfaces	1 x HP iLO 2 x LAN (10Gigabit Ethernet)
Miscellaneous	
Features	Administrator password, power-on password, quick lock
Compliant Standards	ACPI 2.0, WEEE
Pricing Type	CTO
Operating System / Software	

Windows Server Certified	This server is tested, tuned and certified for Windows Server 2008 R2 with OEM-branded hardware. Purchase a Reseller Option Kit to have your server solution pre-loaded.
OS Certified	SunSoft Solaris, SUSE Linux Enterprise Server, Microsoft Windows Server, Red Hat Enterprise Linux
Dimensions & Weight	
Width	5.6 cm
Depth	51 cm
Height	18.2 cm
Weight	5.2 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 90% (non-condensing)