

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	755259-B21-REF

HPE ProLiant DL360 Gen9 - rack-mountable - no CPU - 0 GB - no HDD

Does your data center need a performance driven dense 1U server that you can confidentially deploy for virtualization, data base, or high-performance computing? The HP ProLiant DL360 Gen9 server delivers a 1U chassis with up to two processors delivering an optimal unit that combines high-performance, low energy consumption, improved uptime, and increased density. Manage your DL360 Gen9 server in any IT environment by automating the most essential server lifecycle management tasks: deploy, update, monitor and maintain with ease. The HP ProLiant DL360 Gen9 server is dedicated to meet the most demanding dynamic computing workloads.

Specifikation

General

Status	R4
Type	Server
Recommended Use	Small business, corporate business
Product Form Factor	Rack-mountable - 1U
Embedded Security	Trusted Platform Module (TPM 1.2) Security Chip
Server Scalability	2-way
Front Accessible Bays Qty	1
Hot-Swap Bays Qty	4

Processor / Chipset

CPU	No CPU
Max CPU Qty	2
CPU Upgradability	Upgradable
CPU Socket	FCLGA2011-v3 Socket

RAM

Installed Size	0 GB / 3 TB (max)
Technology	DDR4 SDRAM - Advanced ECC

Form Factor	DIMM 288-pin
Slots	24 (Total) / 24 (empty)
Features	Registered, Load-Reduced DIMM (LRDIMM), HP SmartMemory, Non-Volatile DIMM (NVDIMM)
RAM Supported	3 TB Load-Reduced - Advanced ECC 768 GB registered - Advanced ECC 128 GB Non-Volatile - Advanced ECC

Hard Drive

Type	No HDD
-------------	--------

Storage Controller

Type	1 x SATA
Controller Interface Type	SATA 6Gb/s
Storage Controller Name	HP Dynamic Smart Array B140i
Channel Qty	10
RAID Level	RAID 0, RAID 1, RAID 5, RAID 10

Optical Storage

Type	No optical drive
-------------	------------------

Monitor

Monitor Type	None.
---------------------	-------

Graphics Controller

Type	Integrated
Graphics Processor	Matrox G200
Video Interfaces	VGA

Networking

Type	Integrated
Ethernet Ports	4 x Gigabit Ethernet
Ethernet Controller	HP 331i
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Controller	Integrated Lights-Out 4
Features	Wake on LAN (WoL), PXE support
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

Expansion / Connectivity

Bays	1 (total) / 1 (free) x external 4 (total) / 4 (free) x hot-swap 3.5" LFF
Slots	1 (total) / 1 (free) x PCIe 3.0 x16 - three-quarter-length, full-height 1 (total) / 1 (free) x PCIe 3.0 x8 - low-profile 1 (total) / 1 (free) x FlexibleLOM 1 (total) / 1 (free) x microSD Card (internal)
Interfaces	1 x VGA 1 x serial 4 x LAN (Gigabit Ethernet) 1 x HP iLO 5 x USB 3.0 (1 front, 2 rear, 2 internal)

Miscellaneous

Features	Administrator password, power-on password, keyboard password, serial port I/O control, quick lock, UEFI BIOS
Compliant Standards	ACPI 2.0b, FCC Class A certified, EN 61000-3-2, EN55022, ICES-003, EN 61000-3-3, EN55024, CISPR 22, FCC CFR47 Part 15, IEC 60950-1, EN 60950-1, WEEE, GB 9254, ASHRAE, CNS 13438
Pricing Type	CTO
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	0
Max Supported Qty	2
Operating System / Software	
OS Certified	SUSE Linux Enterprise Server, Microsoft Windows Server, Red Hat Enterprise Linux, Oracle Solaris, Citrix XenServer, Canonical Ubuntu
Dimensions & Weight	
Width	43.46 cm
Depth	75 cm
Height	4.32 cm
Weight	13.77 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)