

## Produktinformation



### Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	867961-B21R

## HPE ProLiant DL360 Gen10 Entry - rack-mountable - Xeon Bronze 3106 1.7 GHz - 16 GB - no HDD

The HPE ProLiant DL360 Gen10 server delivers security, agility and flexibility without compromise. Deploy, update, monitor and maintain with ease.

## Specifikation

### General

<b>Status</b>	W2
<b>Type</b>	Server
<b>Product Form Factor</b>	Rack-mountable - 1U
<b>Built-in Devices</b>	Battery
<b>Server Scalability</b>	2-way
<b>Hot-Swap Bays Qty</b>	8

### Processor / Chipset

<b>CPU</b>	Intel Xeon Bronze 3106 / 1.7 GHz
<b>Number of Cores</b>	8-core
<b>CPU Qty</b>	1
<b>Max CPU Qty</b>	2
<b>CPU Upgradability</b>	Upgradable
<b>CPU Socket</b>	FCLGA3647 Socket
<b>Chipset Type</b>	Intel C621

### Cache Memory

<b>Installed Size</b>	L3 Cache - 11 MB
<b>Cache Per Processor</b>	11 MB

### RAM

<b>Installed Size</b>	16 GB / 1.5 TB (max)
<b>Technology</b>	DDR4 SDRAM - Advanced ECC
<b>Effective Memory Speed</b>	2133 MHz
<b>Rated Memory Speed</b>	2666 MHz
<b>Memory Specification Compliance</b>	PC4-21333
<b>Form Factor</b>	DIMM 288-pin
<b>Slots</b>	24 (Total) / 23 (empty)
<b>Features</b>	Registered, dual rank, slots 13 - 24 are available in two-processor configuration only
<b>Configuration Features</b>	1 x 16 GB
<b>RAM Supported</b>	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC

#### Hard Drive

<b>Type</b>	No HDD
-------------	--------

#### Storage Controller

<b>Type</b>	1 x SATA
<b>Controller Interface Type</b>	SATA 6Gb/s
<b>Storage Controller Name</b>	HPE Smart Array S100i
<b>Channel Qty</b>	14

#### Optical Storage

<b>Type</b>	No optical drive
-------------	------------------

#### Card Reader

<b>Type</b>	Card reader
<b>Supported Flash Memory Cards</b>	microSD

#### Monitor

<b>Monitor Type</b>	None.
---------------------	-------

#### Graphics Controller

<b>Video Interfaces</b>	VGA
-------------------------	-----

#### Networking

<b>Ethernet Ports</b>	4 x Gigabit Ethernet
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Remote Management Protocol</b>	SNMP 3, IPMI 2.0, SMASH CLP
<b>Remote Management Controller</b>	Integrated Lights-Out 5
<b>Features</b>	Wake on LAN (WoL), PXE support

#### Expansion / Connectivity

<b>Bays</b>	8 (total) / 8 (free) x hot-swap 2.5" SFF 1 (total) / 1 (free) x external
-------------	--------------------------------------------------------------------------

<b>Slots</b>	1 (total) / 1 (free) x FlexibleLOM (low-profile) 1 (total) / 1 (free) x PCIe 3.0 x16 - full-height 1 (total) / 1 (free) x PCIe 3.0 x8 (low-profile) 1 (total) / 1 (free) x microSD Card (internal)
<b>Interfaces</b>	14 x SATA-600 1 x HP iLO - RJ-45 (1 rear) 1 x VGA (1 rear) 4 x LAN (Gigabit Ethernet) - RJ-45 (4 rear) 1 x HP iLO - Type A (1 in front) 2 x USB 3.0 (2 rear) 1 x PoweredUSB 3.0 (1 in front) 2 x USB 3.0 (1 front, 1 internal)
Miscellaneous	
<b>Included Accessories</b>	HPE Easy Install Rails, CPU standard heatsink, 5 x standard hot plug fans
<b>Cables Included</b>	Power cable
<b>Compliant Standards</b>	AES, WEEE, TLS v1.2, ASHRAE Class A4, ASHRAE Class A3, ACPI 6.1
Power	
<b>Device Type</b>	Power supply - hot-plug
<b>Power Redundancy</b>	Optional
<b>Power Redundancy Scheme</b>	1+1 (with optional power supply)
<b>Installed Qty</b>	1
<b>Max Supported Qty</b>	2
<b>Nominal Voltage</b>	AC 120/230 V (50/60 Hz)
<b>Power Provided</b>	500 Watt
Operating System / Software	
<b>OS Certified</b>	CentOS, Microsoft Windows Server 2012 R2, VMware vSphere 6.0 (ESXi), SuSE Linux Enterprise Server 11 SP4, Microsoft Windows Server 2016, Red Hat Enterprise Linux 7.3, Red Hat Enterprise Linux 6.9, VMware vSphere 6.5 (ESXi), SuSE Linux Enterprise Server 12 SP2, ClearOS
<b>Software</b>	HPE Server UEFI
Manufacturer Warranty	
<b>Service &amp; Support</b>	Limited warranty - parts and labour - 3 years - on-site - response time: next business day Technical support - software application support - 90 days
Dimensions & Weight	
<b>Width</b>	43.46 cm
<b>Depth</b>	70.7 cm
<b>Height</b>	4.29 cm
<b>Weight</b>	13.04 kg
Environmental Parameters	
<b>Min Operating Temperature</b>	10 °C
<b>Max Operating Temperature</b>	35 °C