

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	879938-B21R

HPE ProLiant DL380 Gen10 High Performance - rack-mountable - Xeon Gold 6130 2.1 GHz - 64 GB - no HDD

The HPE ProLiant DL380 Gen10 server delivers advanced security, performance and expandability. It is ideal for any server environment.

Specifikation

General

Status	W2
Type	Server
Product Form Factor	Rack-mountable - 2U
Built-in Devices	Battery
Server Scalability	2-way
Hot-Swap Bays Qty	8

Processor / Chipset

CPU	Intel Xeon Gold 6130 / 2.1 GHz
Max Turbo Speed	3.7 GHz
Number of Cores	16-core
CPU Qty	2
Max CPU Qty	2
CPU Upgradability	Upgradable
Processor Main Features	Hyper-Threading Technology, Intel Turbo Boost Technology 2
CPU Socket	FCLGA3647 Socket
Chipset Type	Intel C621

Cache Memory

Installed Size	L3 Cache - 44 MB
-----------------------	------------------

Cache Per Processor	22 MB
RAM	
Installed Size	64 GB / 1.5 TB (max)
Technology	DDR4 SDRAM - Advanced ECC
Effective Memory Speed	2666 MHz
Rated Memory Speed	2666 MHz
Memory Specification Compliance	PC4-21333
Form Factor	DIMM 288-pin
Slots	24 (Total) / 22 (empty)
Features	Registered, dual rank, HP SmartMemory, 6-channel memory architecture
Configuration Features	2 x 32 GB
RAM Supported	3 TB Load-Reduced - ECC 1.5 TB registered - ECC 192 GB Non-Volatile - ECC
Hard Drive	
Type	No HDD
Storage Controller	
Type	1 x RAID
Controller Interface Type	SATA 6Gb/s / SAS 12Gb/s
Storage Controller Name	HPE Smart Array P408i-a
Channel Qty	8
RAID Level	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10, RAID 50, RAID 60, RAID 1 ADM, RAID 10 ADM
Buffer Size	2 GB
Optical Storage	
Type	DVD-RW DVD-Writer
Monitor	
Monitor Type	None.
Graphics Controller	
Video Memory	16 MB
Video Interfaces	VGA
Networking	
Ethernet Ports	4 x Gigabit Ethernet, 2 x 25 Gigabit Ethernet
Ethernet Controller	HPE 331i, HPE 631FLR
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol	SNMP 3, IPMI 2.0, SMASH CLP
Remote Management Controller	Integrated Lights-Out 5

Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
Bays	1 (total) / 1 (free) x external 8 (total) / 8 (free) x hot-swap 2.5" SFF
Slots	1 (total) / 1 (free) x FlexibleLOM 2 (total) / 2 (free) x PCIe 3.0 x16 - half-length, full-height 4 (total) / 4 (free) x PCIe 3.0 x8 - half-length, full-height 1 (total) / 1 (free) x microSD Card (internal)
Interfaces	4 x LAN (Gigabit Ethernet) - RJ-45 1 x HP iLO - RJ-45 (1 rear) 1 x VGA (1 rear) 8 x SATA-600 / SAS 3.0 1 x HP iLO - Type A (1 in front) 5 x USB 3.0 (1 front, 2 rear, 2 internal) 2 x LAN (25Gigabit Ethernet)
Miscellaneous	
Included Accessories	6 x standard hot plug fans
Compliant Standards	AES, FIPS 140-2, IPv6 Ready, PCI DSS, TLS v1.2, ASHRAE Class A4, ASHRAE Class A3, WEEE 2002/95/EC, ACPI 6.1
Power	
Device Type	Power supply - hot-plug
Installed Qty	2
Max Supported Qty	2
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Provided	800 Watt
Operating System / Software	
OS Certified	CentOS, Microsoft Windows Server 2012 R2, VMware vSphere 6.0 (ESXi), SuSE Linux Enterprise Server 11 SP4, Microsoft Windows Server 2016, Red Hat Enterprise Linux 7.3, Red Hat Enterprise Linux 6.9, VMware vSphere 6.5, SuSE Linux Enterprise Server 12 SP2, ClearOS
Software	HPE Server UEFI
Environmental Standards	
ENERGY STAR Certified	Yes
ENERGY STAR Version	2.1
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 3 years - on-site - response time: next business day
Dimensions & Weight	
Width	44.55 cm
Depth	67.94 cm
Height	8.73 cm
Weight	14.9 kg
Environmental Parameters	
Min Operating Temperature	10 °C

Max Operating Temperature

35 °C

Humidity Range Operating

8 - 90% (non-condensing)