

## Produktinformation



### Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	B7E26B-REF

## HPE StoreVirtual 4530 - Hard drive array - 7.2 TB - 12 bays (SAS-2) - HDD 600 GB x 12 - iSCSI (1 GbE), iSCSI (10 GbE) (external) - rack- mountable - 2U

HP StoreVirtual storage provides a virtualized pool of storage resources to deliver enterprise SAN functionality that enhances virtual environments, simplifies management, and reduces costs. Easy to deploy, grow and maintain, HP StoreVirtual storage ensures that critical business data remain available. The approach to storage provides a unique data protection level across the entire array, reducing vulnerability without driving up costs the way traditional SANs can. You need affordable storage designed for a virtualized infrastructure that's easy to manage, supports continuous data growth, and keeps your business up and running. HP StoreVirtual 4000 storage is a scale-out storage platform that is designed to meet the fluctuating needs of virtualized environments. Intuitive, common management and storage federation meet the need for simplicity and flexibility in today's virtual datacenters. It allows data mobility across tiers, locations, and between physical and virtual storage.

## Specifikation

### General

<b>Status</b>	R4
<b>Device Type</b>	Hard drive array
<b>Enclosure Type</b>	Rack-mountable - 2U

### Chassis

<b>Installed Devices / Modules Qty</b>	12
<b>Supported Devices / Modules Qty</b>	12
<b>Supported Drives</b>	SAS-2

### Storage

<b>Total Array Capacity</b>	7.2 TB
<b>HDD Array External Interface</b>	iSCSI (1 GbE), iSCSI (10 GbE)

### Processor

<b>CPU</b>	1 x Xeon 2 GHz
------------	----------------

RAM	
Installed Size	64 GB
Storage Controller	
Type	RAID
Cache / Buffer Size (Max)	2 GB
RAID Level	RAID 5, RAID 6, RAID 10
Hard Drive	
Type	HDD - hot-swap
Capacity	12 x 600 GB
Interface Type	SAS 6Gb/s
Spindle Speed	15000 rpm
Expansion / Connectivity	
Expansion Bays	12 (total) / 0 (free) x hot-swap - 3.5" LFF
Expansion Slots	24 x DIMM 240-pin
Interfaces	4 x Ethernet 1000 1 x serial 1 x VGA 1 x management - RJ-45 4 x USB 2 x Ethernet 10Gb
Miscellaneous	
Software Included	LeftHand SAN/iQ Storage Clustering, LeftHand SAN/iQ Network RAID, LeftHand SAN/iQ Thin Provisioning, LeftHand SAN/iQ Snapshots, LeftHand SAN/iQ Remote Copy, LeftHand SAN/iQ Multi-Site/DR Solution Pack, HP Smart Array Advanced Pack 2.0
Compliant Standards	FCC Class A certified, EN 61000-3-2, EN55022, ICES-003, EN 61000-3-3, EN55024, CISPR 22, RoHS, FCC CFR47 Part 15, IEC 60950-1, EN 60950-1, WEEE, BSMI CNS 13438
Power	
Power Device	2 x internal power supply - hot-plug
Max Supported Qty	2
Power Redundancy	Yes
Power Redundancy Scheme	1+1
Voltage Required	AC 120/230 V
Power Provided	750 Watt
Dimensions & Weight	
Width	44.55 cm
Depth	74.93 cm
Height	8.73 cm
Weight	27.27 kg
Environmental Parameters	
Min Operating Temperature	10 °C

Max Operating Temperature	35 °C
Humidity Range Operating	10 - 90% (non-condensing)