

## Produktinformation



### Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	C8R12AR

## HPE Modular Smart Array 2040 LFF Chassis - Storage enclosure - 12 bays (SAS-2) - rack-mountable - 2U - for Modular Smart Array 2040, 2040 10Gb

The HP MSA 2040, a high-performance storage array designed for entry-level HP customers desiring 8 and/or 16 Gb Fiber Channel connectivity with 4 host ports per controller. This excellent MSA 2040 storage array provides an excellent value for customers needing performance balanced with price to support initiatives such as consolidation and virtualization. The HP MSA 2040 storage system brings the performance benefits of SSD drives to MSA array family customers. This array has been designed to maximize performance by using high performance drives across all applications sharing the array. The HP MSA 2040 storage arrays are positioned to provide an excellent value for customers needing increasing performance to support initiatives such as consolidation and virtualization.

## Specifikation

### General

<b>Status</b>	W2
<b>Device Type</b>	Storage enclosure
<b>Enclosure Type</b>	Rack-mountable - 2U

### Chassis

<b>Installed Devices / Modules Qty</b>	0
<b>Supported Devices / Modules Qty</b>	12
<b>Supported Drives</b>	SAS-2

### Processor

<b>CPU</b>	No CPU
------------	--------

### Expansion / Connectivity

<b>Expansion Bays</b>	12 (total) / 12 (free) - 3.5" LFF
-----------------------	-----------------------------------

### Miscellaneous

<b>Compliant Standards</b>	CISPR 22 Class A, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, GS, EN 61000-3-3, EN55022 Class A, CCC, ICES-003 Class A, UL 60950-1, IEC 60950-1, EN 60950-1, WEEE, RoHS, FCC
----------------------------	--

Part 15 A, EN55024 Class A, CAN/CSA C22.2 No. 60950-1-03, VCCI Class A

**Pricing Type** Remarketed

Power

<b>Power Device</b>	2 x internal power supply - hot-plug
<b>Max Supported Qty</b>	2
<b>Power Redundancy</b>	Yes
<b>Power Redundancy Scheme</b>	1+1
<b>Voltage Required</b>	AC 120/230 V - 50 - 60 Hz

Dimensions & Weight

<b>Width</b>	44.7 cm
<b>Depth</b>	57.2 cm
<b>Height</b>	8.9 cm
<b>Weight</b>	14.1 kg

Environmental Parameters

<b>Min Operating Temperature</b>	5 °C
<b>Max Operating Temperature</b>	40 °C
<b>Humidity Range Operating</b>	10 - 90% (non-condensing)

Compatibility Information

<b>Designed For</b>	HPE Modular Smart Array 2040 10Gb iSCSI Dual Controller SFF Bundle, 2040 FC Dual Controller SFF Bundle, 2040 SAS Dual Controller SFF Bundle
---------------------	---

<b>Designed For</b>	HPE Modular Smart Array 2040 10Gb iSCSI Dual Controller SFF Bundle, 2040 FC Dual Controller SFF Bundle, 2040 SAS Dual Controller SFF Bundle
---------------------	---