

Produktinformation



Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	J9359A-REF

HPE MSM422 Access Point WW - Radio access point - GigE

HP MultiService Mobility Access Points (MSM APs) bring intelligence to the network edge by providing scalable, seamless wireless access anywhere, anytime. Their feature set is abundantly rich, dispensing multiple network services, enforcing robust security, and delivering high-performance client access - unlike "thin" or "lite" access points. An integral component of the HP Intelligent Mobility Solution, MSM APs supports a plug-and-play automatic configuration and ongoing central control by MultiService Mobility Controllers for the highest degree of configurability and ease of management.

Specifikation

General

Status	R4
Device Type	Radio access point
Width	22.4 cm
Depth	17 cm
Height	6.6 cm
Weight	1.8 kg

Networking

Form Factor	External
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n (draft 2.0)
Communication Mode	Half-duplex, full-duplex
Features	Auto-uplink (auto MDI/MDI-X), MIMO technology, Wi-Fi Multimedia (WMM) support, Port Aggregation Protocol (PAgP) support
Encryption Algorithm	TLS, PEAP, TTLS, WPA-Enterprise, WPA2-Enterprise
Authentication Method	MS-CHAP v.2

Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.11b, IEEE 802.11a, IEEE 802.3af, IEEE 802.11d, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11h, IEEE 802.11n (draft 2.0)
Aerial	
Antenna Qty	2
Directivity	Omni-directional
Expansion / Connectivity	
Interfaces	1 x 1000Base-T - RJ-45 1 x management - DB-9 2 x aerial
Miscellaneous	
Compliant Standards	EN55022 Class B, ICES-003 Class B, FCC Part 15 B, FCC Part 15.247, OET 65 C, RSS-210, RSS-102, MIC, UL 2043, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1-03, EN 300.489.1, FCC Part 15.407, ARIB STD-T66, ARIB STD-T71, RCR STD-33, EN 300 328, EN 301 893, EN 301 489-17
Power	
Power Over Ethernet (PoE) Supported	PoE
Power Consumption Operational	12 Watt
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	0 - 95%