

## Produktinformation



### Information

<i>Tillverkare</i>	Hewlett Packard Enterprise
<i>Artnr</i>	J9379A-REF

## HPE MSM310 Access Point WW - Radio access point - 100Mb LAN - Wi-Fi

The HP E-series MSM Access Points are managed by any of the HP E-series MSM controllers and the HP RF manager for the RF security sensors. The HP E-series Access Points can also work in autonomous mode. The HP E-series MSM Access Points are IEEE802.3af compliant.

## Specifikation

### General

<b>Status</b>	R4
<b>Device Type</b>	Radio access point
<b>Width</b>	16.3 cm
<b>Depth</b>	16.9 cm
<b>Height</b>	4.8 cm
<b>Weight</b>	1.4 kg

### Networking

<b>Form Factor</b>	External
<b>Connectivity Technology</b>	Wireless, wired
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g
<b>Communication Mode</b>	Half-duplex, full-duplex
<b>Features</b>	Wi-Fi Multimedia (WMM) support
<b>Encryption Algorithm</b>	TLS, PEAP, TTLS, WPA-Enterprise, WPA2-Enterprise
<b>Authentication Method</b>	MS-CHAP v.2
<b>Compliant Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.11b, IEEE 802.11a, IEEE 802.3af, IEEE 802.11d, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11h

### Aerial

<b>Antenna</b>	External detachable
----------------	---------------------

<b>Antenna Qty</b>	2
<b>Directivity</b>	Omni-directional
<b>Gain Level</b>	2 dBi

Expansion / Connectivity

<b>Interfaces</b>	2 x 100Base-TX - RJ-45 1 x management - DB-9 2 x aerial
-------------------	---

Miscellaneous

<b>Compliant Standards</b>	EN55022 Class B, ICES-003 Class B, FCC Part 15 B, FCC Part 15.247, OET 65 C, RSS-210, RSS-102, MIC, UL 2043, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1-03, EN 300.489.1, FCC Part 15.407, ARIB STD-T66, ARIB STD-T71, RCR STD-33, EN 300 328, EN 301 893, EN 301 489-17
----------------------------	--

Power

<b>Power Over Ethernet (PoE) Supported</b>	PoE
<b>Power Consumption Operational</b>	6.5 Watt

Environmental Parameters

<b>Min Operating Temperature</b>	0 °C
<b>Max Operating Temperature</b>	45 °C
<b>Humidity Range Operating</b>	0 - 95%